JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class PreferenceChangeEvent

java.lang.Object
  java.util.EventObject
    java.util.prefs.PreferenceChangeEvent

All Implemented Interfaces:

Serializable

```
public class PreferenceChangeEvent
extends EventObject
```

An event emitted by a `Preferences` node to indicate that a preference has been added, removed or has had its value changed.

Note, that although PreferenceChangeEvent inherits Serializable interface from EventObject, it is not intended to be Serializable. Appropriate serialization methods are implemented to throw NotSerializableException.

Since:

1.4

See Also:

`Preferences`, `PreferenceChangeListener`, `NodeChangeEvent`

Field Summary

Fields declared in class EventObject
`source`

Constructor Summary

Constructors

Constructor	Description
`PreferenceChangeEvent``(Preferences node, String key, String newValue)`	Constructs a new `PreferenceChangeEvent` instance.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`String`	**`getKey`**`()`	

		Returns the key of the preference that was changed.
String	**getNewValue**()	Returns the new value for the preference.
Preferences	**getNode**()	Returns the preference node that emitted the event.

Methods declared in class EventObject

getSource, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

PreferenceChangeEvent

```
public PreferenceChangeEvent(Preferences node,
                             String key,
                             String newValue)
```

Constructs a new `PreferenceChangeEvent` instance.

Parameters:

`node` - The Preferences node that emitted the event.

`key` - The key of the preference that was changed.

`newValue` - The new value of the preference, or `null` if the preference is being removed.

Method Details

getNode

```
public Preferences getNode()
```

Returns the preference node that emitted the event.

Returns:

The preference node that emitted the event.

getKey

```
public String getKey()
```

Returns the key of the preference that was changed.

Returns:

The key of the preference that was changed.

getNewValue

```
public String getNewValue()
```

Returns the new value for the preference.

Returns:

The new value for the preference, or `null` if the preference was removed.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.