JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class CalendarDataProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.util.spi.CalendarDataProvider

```
public abstract class CalendarDataProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide locale-dependent `Calendar` parameters.

Since:

1.8

See Also:

`CalendarNameProvider`

Constructor Summary

Constructors

Modifier	Constructor	Description
`protected`	`CalendarDataProvider()`	Sole constructor.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`abstract int`	`getFirstDayOfWeek(Locale locale)`	Returns the first day of a week in the given `locale`.
`abstract int`	`getMinimalDaysInFirstWee(Locale locale)`	Returns the minimal number of days required in the first week of a year.

Methods declared in class LocaleServiceProvider

`getAvailableLocales`, `isSupportedLocale`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

CalendarDataProvider

```
protected CalendarDataProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Details

getFirstDayOfWeek

```
public abstract int getFirstDayOfWeek(Locale locale)
```

Returns the first day of a week in the given `locale`. This information is required by `Calendar` to support operations on the week-related calendar fields.

Parameters:

`locale` - the desired locale

Returns:

the first day of a week; one of `Calendar.SUNDAY` .. `Calendar.SATURDAY`, or 0 if the value isn't available for the `locale`

Throws:

`NullPointerException` - if `locale` is `null`.

See Also:

`Calendar.getFirstDayOfWeek()`, First Week

getMinimalDaysInFirstWeek

```
public abstract int getMinimalDaysInFirstWeek(Locale locale)
```

Returns the minimal number of days required in the first week of a year. This information is required by `Calendar` to determine the first week of a year. Refer to the description of how `Calendar` determines the first week.

Parameters:

`locale` - the desired locale

Returns:

the minimal number of days of the first week, or 0 if the value isn't available for the `locale`

Throws:

`NullPointerException` - if `locale` is `null`.

See Also:

`Calendar.getMinimalDaysInFirstWeek()`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.