JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class CurrencyNameProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.util.spi.CurrencyNameProvider

```
public abstract class CurrencyNameProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide localized currency symbols and display names for the `Currency` class. Note that currency symbols are considered names when determining behaviors described in the `LocaleServiceProvider` specification.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**CurrencyNameProvider**()	Sole constructor.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
String	**getDisplayName**(String currencyCode, Locale locale)	Returns a name for the currency that is appropriate for display to the user.
abstract String	**getSymbol**(String currencyCode, Locale locale)	Gets the symbol of the given currency code for the specified locale.

Methods declared in class LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

CurrencyNameProvider

```
protected CurrencyNameProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Details

getSymbol

```
public abstract String getSymbol(String currencyCode,
                                 Locale locale)
```

Gets the symbol of the given currency code for the specified locale. For example, for "USD" (US Dollar), the symbol is "$" if the specified locale is the US, while for other locales it may be "US$". If no symbol can be determined, null should be returned.

Parameters:

`currencyCode` - the ISO 4217 currency code, which consists of three upper-case letters between 'A' (U+0041) and 'Z' (U+005A)

`locale` - the desired locale

Returns:

the symbol of the given currency code for the specified locale, or null if the symbol is not available for the locale

Throws:

`NullPointerException` - if `currencyCode` or `locale` is null

`IllegalArgumentException` - if `currencyCode` is not in the form of three upper-case letters, or `locale` isn't one of the locales returned from `getAvailableLocales()`.

See Also:

`Currency.getSymbol(java.util.Locale)`

getDisplayName

```
public String getDisplayName(String currencyCode,
                             Locale locale)
```

Returns a name for the currency that is appropriate for display to the user. The default implementation returns null.

Parameters:

`currencyCode` - the ISO 4217 currency code, which consists of three upper-case letters between 'A' (U+0041) and 'Z' (U+005A)

`locale` - the desired locale

Returns:

the name for the currency that is appropriate for display to the user, or null if the name is not available for the locale

Throws:

`IllegalArgumentException` - if `currencyCode` is not in the form of three upper-case letters, or `locale` isn't one of the locales returned from `getAvailableLocales()`.

`NullPointerException` - if `currencyCode` or `locale` is `null`

Since:

1.7

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.