JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class LocaleNameProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.util.spi.LocaleNameProvider

```
public abstract class LocaleNameProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide localized names for the `Locale` class.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**LocaleNameProvider**()	Sole constructor.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
abstract String	**getDisplayCountry**(String countryCode, Locale locale)	Returns a localized name for the given IETF BCP47 region code (either ISO 3166 country code or UN M.49 area codes) and the given locale that is appropriate for display to the user.
abstract String	**getDisplayLanguage**(String languageCode, Locale locale)	Returns a localized name for the given IETF BCP47 language code and the given locale that is appropriate for display to the user.
String	**getDisplayScript**(String scriptCode, Locale locale)	Returns a localized name for the given IETF BCP47 script code and

		the given locale that is appropriate for display to the user.
String	**getDisplayUnicodeExtensi**(String key, Locale locale)	Returns a localized name for the given Unicode extension key, and the given locale that is appropriate for display to the user.
String	**getDisplayUnicodeExtensi**(String type, String key, Locale locale)	Returns a localized name for the given Unicode extension type, and the given locale that is appropriate for display to the user.
abstract String	**getDisplayVariant**(String variant, Locale locale)	Returns a localized name for the given variant code and the given locale that is appropriate for display to the user.

Methods declared in class LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

LocaleNameProvider

```
protected LocaleNameProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Details

getDisplayLanguage

```
public abstract String getDisplayLanguage(String languageCode,
                                          Locale locale)
```

Returns a localized name for the given IETF BCP47 language code and the given locale that is appropriate for display to the user. For example, if `languageCode` is "fr" and `locale` is en_US, getDisplayLanguage() will return "French"; if `languageCode` is "en" and `locale` is fr_FR, getDisplayLanguage() will return "anglais". If the name returned cannot be localized according to `locale`, (say, the provider does not have a Japanese name for Croatian), this method returns null.

Parameters:

`languageCode` - the language code string in the form of two to eight lower-case letters between 'a' (U+0061) and 'z' (U+007A)

`locale` - the desired locale

Returns:

the name of the given language code for the specified locale, or null if it's not available.

Throws:

`NullPointerException` - if `languageCode` or `locale` is null

`IllegalArgumentException` - if `languageCode` is not in the form of two or three lower-case letters, or `locale` isn't one of the locales returned from `getAvailableLocales()`.

See Also:

`Locale.getDisplayLanguage(java.util.Locale)`

getDisplayScript

```
public String getDisplayScript(String scriptCode,
                               Locale locale)
```

Returns a localized name for the given IETF BCP47 script code and the given locale that is appropriate for display to the user. For example, if `scriptCode` is "Latn" and `locale` is en_US, getDisplayScript() will return "Latin"; if `scriptCode` is "Cyrl" and `locale` is fr_FR, getDisplayScript() will return "cyrillique". If the name returned cannot be localized according to `locale`, (say, the provider does not have a Japanese name for Cyrillic), this method returns null. The default implementation returns null.

Parameters:

`scriptCode` - the four letter script code string in the form of title-case letters (the first letter is upper-case character between 'A' (U+0041) and 'Z' (U+005A) followed by three lower-case character between 'a' (U+0061) and 'z' (U+007A)).

`locale` - the desired locale

Returns:

the name of the given script code for the specified locale, or null if it's not available.

Throws:

`NullPointerException` - if `scriptCode` or `locale` is null

`IllegalArgumentException` - if `scriptCode` is not in the form of four title case letters, or `locale` isn't one of the locales returned from `getAvailableLocales()`.

Since:

1.7

See Also:

`Locale.getDisplayScript(java.util.Locale)`

getDisplayCountry

```
public abstract String getDisplayCountry(String countryCode,
                                         Locale locale)
```

Returns a localized name for the given IETF BCP47 region code (either ISO 3166 country code or UN M.49 area codes) and the given locale that is appropriate for display to the user. For example, if `countryCode` is "FR" and `locale` is en_US, getDisplayCountry() will return "France"; if `countryCode` is "US" and `locale` is fr_FR, getDisplayCountry() will return "Etats-Unis". If the name returned cannot be localized according to `locale`, (say, the provider does not have a Japanese name for Croatia), this method returns null.

Parameters:

`countryCode` - the country(region) code string in the form of two upper-case letters between 'A' (U+0041) and 'Z' (U+005A) or the UN M.49 area code in the form of three digit letters between '0' (U+0030) and '9' (U+0039).

`locale` - the desired locale

Returns:

the name of the given country code for the specified locale, or null if it's not available.

Throws:

`NullPointerException` - if `countryCode` or `locale` is null

IllegalArgumentException - if countryCode is not in the form of two upper-case letters or three digit letters, or locale isn't one of the locales returned from getAvailableLocales().

See Also:

Locale.getDisplayCountry(java.util.Locale)

getDisplayVariant

```
public abstract String getDisplayVariant(String variant,
                                         Locale locale)
```

Returns a localized name for the given variant code and the given locale that is appropriate for display to the user. If the name returned cannot be localized according to locale, this method returns null.

Parameters:

variant - the variant string

locale - the desired locale

Returns:

the name of the given variant string for the specified locale, or null if it's not available.

Throws:

NullPointerException - if variant or locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

Locale.getDisplayVariant(java.util.Locale)

getDisplayUnicodeExtensionKey

```
public String getDisplayUnicodeExtensionKey(String key,
                                            Locale locale)
```

Returns a localized name for the given Unicode extension key, and the given locale that is appropriate for display to the user. If the name returned cannot be localized according to locale, this method returns null.

Implementation Requirements:

the default implementation returns null.

Parameters:

key - the Unicode Extension key, not null.

locale - the desired locale, not null.

Returns:

the name of the given key string for the specified locale, or null if it's not available.

Throws:

`NullPointerException` - if `key` or `locale` is null

`IllegalArgumentException` - if `locale` isn't one of the locales returned from `getAvailableLocales()`.

Since:

10

getDisplayUnicodeExtensionType

```
public String getDisplayUnicodeExtensionType(String type,
                                             String key,
                                             Locale locale)
```

Returns a localized name for the given Unicode extension type, and the given locale that is appropriate for display to the user. If the name returned cannot be localized according to `locale`, this method returns null.

Implementation Requirements:

the default implementation returns `null`.

Parameters:

`type` - the Unicode Extension type, not null.

`key` - the Unicode Extension key for this `type`, not null.

`locale` - the desired locale, not null.

Returns:

the name of the given type string for the specified locale, or null if it's not available.

Throws:

`NullPointerException` - if `key`, `type` or `locale` is null

`IllegalArgumentException` - if `locale` isn't one of the locales returned from `getAvailableLocales()`.

Since:

10

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA

94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.