JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class TimeZoneNameProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.util.spi.TimeZoneNameProvider

```
public abstract class TimeZoneNameProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide localized time zone names for the `TimeZone` class. The localized time zone names available from the implementations of this class are also the source for the `DateFormatSymbols.getZoneStrings()` method.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**TimeZoneNameProvider**()	Sole constructor.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
abstract String	**getDisplayName**(String ID, boolean daylight, int style, Locale locale)	Returns a name for the given time zone ID that's suitable for presentation to the user in the specified locale.
String	**getGenericDisplayName**(String ID, int style, Locale locale)	Returns a generic name for the given time zone ID that's suitable for presentation to the user in the specified locale.

Methods declared in class LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

TimeZoneNameProvider

```
protected TimeZoneNameProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Details

getDisplayName

```
public abstract String getDisplayName(String ID,
                                      boolean daylight,
                                      int style,
                                      Locale locale)
```

Returns a name for the given time zone ID that's suitable for presentation to the user in the specified locale. The given time zone ID is "GMT" or one of the names defined using "Zone" entries in the "tz database", a public domain time zone database at https://www.iana.org/time-zones. The data of this database is contained in a file whose name starts with "tzdata", and the specification of the data format is part of the zic.8 man page, which is contained in a file whose name starts with "tzcode".

If `daylight` is true, the method should return a name appropriate for daylight saving time even if the specified time zone has not observed daylight saving time in the past.

Parameters:

`ID` - a time zone ID string

`daylight` - if true, return the daylight saving name.

`style` - either `TimeZone.LONG` or `TimeZone.SHORT`

`locale` - the desired locale

Returns:

the human-readable name of the given time zone in the given locale, or null if it's not available.

Throws:

IllegalArgumentException - if style is invalid, or locale isn't one of the locales returned from getAvailableLocales().

NullPointerException - if ID or locale is null

External Specifications

Time Zone Database

See Also:

TimeZone.getDisplayName(boolean, int, java.util.Locale)

getGenericDisplayName

```
public String getGenericDisplayName(String ID,
                                     int style,
                                     Locale locale)
```

Returns a generic name for the given time zone ID that's suitable for presentation to the user in the specified locale. Generic time zone names are neutral from standard time and daylight saving time. For example, "PT" is the short generic name of time zone ID America/Los_Angeles, while its short standard time and daylight saving time names are "PST" and "PDT", respectively. Refer to getDisplayName for valid time zone IDs.

The default implementation of this method returns null.

Parameters:

ID - a time zone ID string

style - either TimeZone.LONG or TimeZone.SHORT

locale - the desired locale

Returns:

the human-readable generic name of the given time zone in the given locale, or null if it's not available.

Throws:

IllegalArgumentException - if style is invalid, or locale isn't one of the locales returned from getAvailableLocales().

NullPointerException - if ID or locale is null

Since:

1.8

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other

countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.