JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Adler32

java.lang.Object
    java.util.zip.Adler32

All Implemented Interfaces:

Checksum

```
public class Adler32
extends Object
implements Checksum
```

A class that can be used to compute the Adler-32 checksum of a data stream. An Adler-32 checksum is almost as reliable as a CRC-32 but can be computed much faster.

Passing a `null` argument to a method in this class will cause a `NullPointerException` to be thrown.

Since:

1.1

Constructor Summary

Constructors

Constructor	Description
`Adler32()`	Creates a new Adler32 object.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`long`	`getValue()`	Returns the checksum value.
`void`	`reset()`	Resets the checksum to initial value.
`void`	`update(byte[] b, int off, int len)`	Updates the checksum with the specified array of bytes.
`void`	`update(int b)`	Updates the checksum with the specified byte

		(the low eight bits of the argument b).
void	**update**(ByteBuffer buffer)	Updates the checksum with the bytes from the specified buffer.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods declared in interface Checksum

update

Constructor Details

Adler32

```
public Adler32()
```

Creates a new Adler32 object.

Method Details

update

```
public void update(int b)
```

Updates the checksum with the specified byte (the low eight bits of the argument b).

Specified by:

update in interface Checksum

Parameters:

b - the byte to update the checksum with

update

```
public void update(byte[] b,
                   int off,
                   int len)
```

Updates the checksum with the specified array of bytes.

Specified by:

`update` in interface `Checksum`

Parameters:

`b` - the byte array to update the checksum with

`off` - the start offset of the data

`len` - the number of bytes to use for the update

Throws:

`ArrayIndexOutOfBoundsException` - if `off` is negative, or `len` is negative, or `off+len` is negative or greater than the length of the array `b`.

update

```
public void update(ByteBuffer buffer)
```

Updates the checksum with the bytes from the specified buffer. The checksum is updated with the remaining bytes in the buffer, starting at the buffer's position. Upon return, the buffer's position will be updated to its limit; its limit will not have been changed.

Specified by:

`update` in interface `Checksum`

Parameters:

`buffer` - the ByteBuffer to update the checksum with

Since:

1.8

reset

```
public void reset()
```

Resets the checksum to initial value.

Specified by:

`reset` in interface `Checksum`

getValue

```
public long getValue()
```

Returns the checksum value.

Specified by:

`getValue` in interface `Checksum`

Returns:

the current checksum value

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.