JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class CheckedInputStream

java.lang.Object
  java.io.InputStream
    java.io.FilterInputStream
      java.util.zip.CheckedInputStream

All Implemented Interfaces:

Closeable, AutoCloseable

```
public class CheckedInputStream
extends FilterInputStream
```

An input stream that also maintains a checksum of the data being read. The checksum can then be used to verify the integrity of the input data.

Since:

1.1

See Also:

Checksum

Field Summary

Fields declared in class FilterInputStream
in

Constructor Summary

Constructors

Constructor	Description
CheckedInputStream(InputStream in, Checksum cksum)	Creates an input stream using the specified Checksum.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
Checksum	**getChecksum**()	Returns the Checksum for this input stream.
int	**read**()	Reads a byte.

int	**read**(byte[] buf, int off, int len)	Reads into an array of bytes.
long	**skip**(long n)	Skips specified number of bytes of input.

Methods declared in class FilterInputStream

available, close, mark, markSupported, read, reset

Methods declared in class InputStream

nullInputStream, readAllBytes, readNBytes, readNBytes, skipNBytes, transferTo

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

CheckedInputStream

```
public CheckedInputStream(InputStream in,
                          Checksum cksum)
```

Creates an input stream using the specified Checksum.

Parameters:

in - the input stream

cksum - the Checksum

Method Details

read

```
public int read()
         throws IOException
```

Reads a byte. Will block if no input is available.

Overrides:

read in class FilterInputStream

Returns:

the byte read, or -1 if the end of the stream is reached.

Throws:

`IOException` - if an I/O error has occurred

See Also:

`FilterInputStream.in`

read

```
public int read(byte[] buf,
                int off,
                int len)
         throws IOException
```

Reads into an array of bytes. If `len` is not zero, the method blocks until some input is available; otherwise, no bytes are read and `0` is returned.

Overrides:

`read` in class `FilterInputStream`

Parameters:

`buf` - the buffer into which the data is read

`off` - the start offset in the destination array `b`

`len` - the maximum number of bytes read

Returns:

the actual number of bytes read, or -1 if the end of the stream is reached.

Throws:

`NullPointerException` - If `buf` is `null`.

`IndexOutOfBoundsException` - If `off` is negative, `len` is negative, or `len` is greater than `buf.length - off`

`IOException` - if an I/O error has occurred

See Also:

`FilterInputStream.in`

skip

```
public long skip(long n)
          throws IOException
```

Skips specified number of bytes of input.

Overrides:

`skip` in class `FilterInputStream`

Parameters:

n - the number of bytes to skip

Returns:

the actual number of bytes skipped

Throws:

`IOException` - if an I/O error has occurred

See Also:

`InputStream.skipNBytes(long)`

getChecksum

```
public Checksum getChecksum()
```

Returns the Checksum for this input stream.

Returns:

the Checksum value

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.