JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class GZIPOutputStream

java.lang.Object
  java.io.OutputStream
    java.io.FilterOutputStream
      java.util.zip.DeflaterOutputStream
        java.util.zip.GZIPOutputStream

All Implemented Interfaces:

`Closeable`, `Flushable`, `AutoCloseable`

```
public class GZIPOutputStream
extends DeflaterOutputStream
```

This class implements a stream filter for writing compressed data in the GZIP file format.

Unless otherwise noted, passing a `null` argument to a constructor or method in this class will cause a `NullPointerException` to be thrown.

Since:

1.1

Field Summary

Fields

Modifier and Type	Field	Description
protected CRC32	**crc**	CRC-32 of uncompressed data.

Fields declared in class DeflaterOutputStream

`buf`, `def`

Fields declared in class FilterOutputStream

`out`

Constructor Summary

Constructors

Constructor	Description
GZIPOutputStream(OutputStream out)	Creates a new output stream with a default buffer size.

GZIPOutputStream(OutputStream out, boolean syncFlush)	Creates a new output stream with a default buffer size and the specified flush mode.
GZIPOutputStream(OutputStream out, int size)	Creates a new output stream with the specified buffer size.
GZIPOutputStream(OutputStream out, int size, boolean syncFlush)	Creates a new output stream with the specified buffer size and flush mode.

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
void	**finish**()	Finishes writing compressed data to the output stream without closing the underlying stream.
void	**write**(byte[] buf, int off, int len)	Writes array of bytes to the compressed output stream.

Methods declared in class DeflaterOutputStream

close, deflate, flush, write

Methods declared in class FilterOutputStream

write

Methods declared in class OutputStream

nullOutputStream

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Details

crc

```
protected CRC32 crc
```

CRC-32 of uncompressed data.

Constructor Details

GZIPOutputStream

```
public GZIPOutputStream(OutputStream out,
                        int size)
                 throws IOException
```

Creates a new output stream with the specified buffer size.

The new output stream instance is created as if by invoking the 3-argument constructor GZIPOutputStream(out, size, false).

Parameters:

`out` - the output stream

`size` - the output buffer size

Throws:

`IOException` - If an I/O error has occurred.

`IllegalArgumentException` - if `size <= 0`

GZIPOutputStream

```
public GZIPOutputStream(OutputStream out,
                        int size,
                        boolean syncFlush)
                 throws IOException
```

Creates a new output stream with the specified buffer size and flush mode.

Parameters:

`out` - the output stream

`size` - the output buffer size

syncFlush - if true invocation of the inherited flush() method of this instance flushes the compressor with flush mode Deflater.SYNC_FLUSH before flushing the output stream, otherwise only flushes the output stream

Throws:

IOException - If an I/O error has occurred.

IllegalArgumentException - if size <= 0

Since:

1.7

GZIPOutputStream

```
public GZIPOutputStream(OutputStream out)
                 throws IOException
```

Creates a new output stream with a default buffer size.

The new output stream instance is created as if by invoking the 2-argument constructor GZIPOutputStream(out, false).

Parameters:

out - the output stream

Throws:

IOException - If an I/O error has occurred.

GZIPOutputStream

```
public GZIPOutputStream(OutputStream out,
                        boolean syncFlush)
                 throws IOException
```

Creates a new output stream with a default buffer size and the specified flush mode.

Parameters:

out - the output stream

syncFlush - if true invocation of the inherited flush() method of this instance flushes the compressor with flush mode Deflater.SYNC_FLUSH before flushing the output stream, otherwise only flushes the output stream

Throws:

IOException - If an I/O error has occurred.

Since:

1.7

Method Details

write

```
public void write(byte[] buf,
                  int off,
                  int len)
           throws IOException
```

Writes array of bytes to the compressed output stream. This method will block until all the bytes are written.

Overrides:

`write` in class `DeflaterOutputStream`

Parameters:

`buf` - the data to be written

`off` - the start offset of the data

`len` - the length of the data

Throws:

`IOException` - If an I/O error has occurred.

See Also:

`FilterOutputStream.write(int)`

finish

```
public void finish()
            throws IOException
```

Finishes writing compressed data to the output stream without closing the underlying stream. Use this method when applying multiple filters in succession to the same output stream.

Overrides:

`finish` in class `DeflaterOutputStream`

Throws:

`IOException` - if an I/O error has occurred

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA

94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.