JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class InflaterOutputStream

java.lang.Object
  java.io.OutputStream
    java.io.FilterOutputStream
      java.util.zip.InflaterOutputStream

All Implemented Interfaces:

Closeable, Flushable, AutoCloseable

```
public class InflaterOutputStream
extends FilterOutputStream
```

Implements an output stream filter for decompressing data stored in the "deflate" compression format.

Decompressor Usage

An `InflaterOutputStream` created without specifying a decompressor will create a decompressor at construction time, and close the decompressor when the output stream is closed or when `finish()` is called.

If a decompressor is specified when creating a `InflaterOutputStream`, it is the responsibility of the caller to close the decompressor after closing the output stream.

API Note:

The `close()` method should be called to release resources used by this stream, either directly, or with the `try`-with-resources statement.

Since:

1.6

See Also:

`InflaterInputStream`, `DeflaterInputStream`, `DeflaterOutputStream`

Field Summary

Fields

Modifier and Type	Field	Description
`protected final byte[]`	**`buf`**	Output buffer for writing decompressed data.
`protected final Inflater`	**`inf`**	Decompressor for this stream.

Fields declared in class FilterOutputStream
out

Constructor Summary

Constructors

Constructor	Description
InflaterOutputStream (OutputStream out)	Creates a new output stream and decompressor with a default buffer size.
InflaterOutputStream (OutputStream out, Inflater infl)	Creates a new output stream with the specified decompressor and a default buffer size.
InflaterOutputStream (OutputStream out, Inflater infl, int bufLen)	Creates a new output stream with the specified decompressor and buffer size.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
void	**close**()	Writes any remaining decompressed data to the output stream and closes the underlying output stream.
void	**finish**()	Writes any pending buffered decompressed data to the underlying output stream, without closing the underlying stream.
void	**flush**()	Flushes this output stream, writing any pending buffered decompressed data to

		the underlying output stream.
void	write(byte[] b, int off, int len)	Writes an array of bytes to the decompressed output stream.
void	write(int b)	Writes a byte to the decompressed output stream.

Methods declared in class FilterOutputStream

write

Methods declared in class OutputStream

nullOutputStream

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Details

inf

```
protected final Inflater inf
```

Decompressor for this stream.

buf

```
protected final byte[] buf
```

Output buffer for writing decompressed data.

Constructor Details

InflaterOutputStream

```
public InflaterOutputStream(OutputStream out)
```

Creates a new output stream and decompressor with a default buffer size.

The decompressor will be closed when this output stream is closed.

Parameters:

`out` - output stream to write the decompressed data to

Throws:

`NullPointerException` - if `out` is null

InflaterOutputStream

```
public InflaterOutputStream(OutputStream out,
                            Inflater infl)
```

Creates a new output stream with the specified decompressor and a default buffer size.

Closing this output stream will not close the given decompressor.

Parameters:

`out` - output stream to write the decompressed data to

`infl` - decompressor ("inflater") for this stream

Throws:

`NullPointerException` - if `out` or `infl` is null

InflaterOutputStream

```
public InflaterOutputStream(OutputStream out,
                            Inflater infl,
                            int bufLen)
```

Creates
a new output stream with the specified decompressor and buffer size.

Closing this output stream will not close the given decompressor.

Parameters:

`out` - output stream to write the decompressed data to

`infl` - decompressor ("inflater") for this stream

`bufLen` - decompression buffer size

Throws:

`IllegalArgumentException` - if `bufLen <= 0`

`NullPointerException` - if `out` or `infl` is null

Method Details

close

```
public void close()
           throws IOException
```

Writes any remaining decompressed data to the output stream and closes the underlying output stream.

Specified by:

`close` in interface `AutoCloseable`

Specified by:

`close` in interface `Closeable`

Overrides:

`close` in class `FilterOutputStream`

Implementation Requirements:

If not already closed, this method calls `finish()` before closing the underlying output stream.

Throws:

`IOException` - if an I/O error occurs

See Also:

`FilterOutputStream.flush()`, `FilterOutputStream.out`

flush

```
public void flush()
           throws IOException
```

Flushes this output stream, writing any pending buffered decompressed data to the underlying output stream.

Specified by:

`flush` in interface `Flushable`

Overrides:

`flush` in class `FilterOutputStream`

Throws:

`IOException` - if an I/O error occurs or this stream is already closed

See Also:

FilterOutputStream.out

finish

```
public void finish()
            throws IOException
```

Writes any pending buffered decompressed data to the underlying output stream, without closing the underlying stream.

Implementation Requirements:

This method calls flush() to write any pending buffered decompressed data.

If this InflaterOutputStream was created without specifying a decompressor, then this method closes the decompressor that was created at construction time. The InflaterOutputStream cannot then be used for any further writes.

Throws:

IOException - if an I/O error occurs or this stream is already closed

write

```
public void write(int b)
           throws IOException
```

Writes a byte to the decompressed output stream.

Overrides:

write in class FilterOutputStream

Parameters:

b - a single byte of compressed data to decompress and write to the output stream

Throws:

IOException - if an I/O error occurs or this stream is already closed

ZipException - if a compression (ZIP) format error occurs

write

```
public void write(byte[] b,
                  int off,
                  int len)
           throws IOException
```

Writes an array of bytes to the decompressed output stream.

Overrides:

`write` in class `FilterOutputStream`

Parameters:

`b` - buffer containing compressed data to decompress and write to the output stream

`off` - starting offset of the compressed data within `b`

`len` - number of bytes to decompress from `b`

Throws:

`IndexOutOfBoundsException` - if `off < 0`, or if `len < 0`, or if `len > b.length - off`

`IOException` - if an I/O error occurs or this stream is already closed

`NullPointerException` - if `b` is null

`ZipException` - if a compression (ZIP) format error occurs

See Also:

`FilterOutputStream.write(int)`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.