JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Interface DataOutput

All Known Subinterfaces:

ImageOutputStream, ObjectOutput

All Known Implementing Classes:

DataOutputStream, FileCacheImageOutputStream, FileImageOutputStream, ImageOutputStreamImpl, MemoryCacheImageOutputStream, ObjectOutputStream, RandomAccessFile

---

```
public interface DataOutput
```

The `DataOutput` interface provides for converting data from any of the Java primitive types to a series of bytes and writing these bytes to a binary stream. There is also a facility for converting a `String` into modified UTF-8 format and writing the resulting series of bytes.

For all the methods in this interface that write bytes, it is generally true that if a byte cannot be written for any reason, an `IOException` is thrown.

Since:

JDK1.0

See Also:

DataInput, DataOutputStream

Method Summary

Abstract Methods

Modifier and Type	Method	Description
void	**write**(byte[] b)	

		Writes to the output stream all the bytes in array b.
void	**write**(byte[] b, int off, int len)	Writes len bytes from array b, in order, to the output stream.
void	**write**(int b)	Writes to the output stream the eight low-order bits of the argument b.
void	**writeBoolean**(boolean v)	Writes a boolean value to this output stream.
void	**writeByte**(int v)	Writes to the output stream the eight low- order bits of the argument v.
void	**writeBytes**(**String** s)	Writes a string to the output stream.
void	**writeChar**(int v)	Writes a char value, which is comprised of two bytes, to the output stream.
void	**writeChars**(**String** s)	Writes every character in the string s, to the output stream, in order, two bytes per character.
void	**writeDouble**(double v)	Writes a double value, which is comprised of eight bytes, to the output stream.
void	**writeFloat**(float v)	Writes a float value, which is comprised of four bytes, to the output stream.
void	**writeInt**(int v)	Writes an int value, which is comprised of four bytes, to the output stream.
void	**writeLong**(long v)	Writes a long value, which is comprised of eight bytes, to the output stream.
void	**writeShort**(int v)	

		Writes two bytes to the output stream to represent the value of the argument.
void	**writeUTF**(**String** s)	Writes two bytes of length information to the output stream, followed by the **modified UTF-8** representation of every character in the string `s`.

Method Detail

write

```
void write(int b)
    throws IOException
```

Writes to the output stream the eight low-order bits of the argument `b`. The 24 high-order bits of `b` are ignored.

Parameters:

`b - the byte to be written.`

Throws:

`IOException - if an I/O error occurs.`

write

```
void write(byte[] b)
    throws IOException
```

Writes to the output stream all the bytes in array `b`. If `b` is `null`, a `NullPointerException` is thrown. If `b.length` is zero, then no bytes are written. Otherwise, the byte `b[0]` is written first, then `b[1]`, and so on; the last byte written is `b[b.length-1]`.

Parameters:

`b - the data.`

Throws:

`IOException - if an I/O error occurs.`

write

```
void write(byte[] b,
           int off,
           int len)
    throws IOException
```

Writes `len` bytes from array `b`, in order, to the output stream. If `b` is `null`, a `NullPointerException` is thrown. If `off` is negative, or `len` is negative, or `off+len` is greater than the length of the array `b`, then an `IndexOutOfBoundsException` is thrown. If `len` is zero, then no bytes are written. Otherwise, the byte `b[off]` is written first, then `b[off+1]`, and so on; the last byte written is `b[off+len-1]`.

Parameters:

`b - the data.`

`off - the start offset in the data.`

`len - the number of bytes to write.`

Throws:

`IOException - if an I/O error occurs.`

writeBoolean

```
void writeBoolean(boolean v)
           throws IOException
```

Writes a `boolean` value to this output stream. If the argument `v` is `true`, the value `(byte)1` is written; if `v` is `false`, the value `(byte)0` is written. The byte written by this method may be read by the `readBoolean` method of interface `DataInput`, which will then return a `boolean` equal to `v`.

Parameters:

`v - the boolean to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeByte

```
void writeByte(int v)
        throws IOException
```

Writes to the output stream the eight low- order bits of the argument `v`. The 24 high-order bits of `v` are ignored. (This means that `writeByte` does exactly the same thing as `write` for an integer argument.) The byte written by this

method may be read by the `readByte` method of interface `DataInput`, which will then return a `byte` equal to `(byte)v`.

Parameters:

`v - the byte value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeShort

```
void writeShort(int v)
         throws IOException
```

Writes two bytes to the output stream to represent the value of the argument. The byte values to be written, in the order shown, are:

```
(byte)(0xff & (v >> 8))
(byte)(0xff & v)
```

The bytes written by this method may be read by the `readShort` method of interface `DataInput` , which will then return a `short` equal to `(short)v`.

Parameters:

`v - the short value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeChar

```
void writeChar(int v)
        throws IOException
```

Writes a `char` value, which is comprised of two bytes, to the output stream. The byte values to be written, in the order shown, are:

```
(byte)(0xff & (v >> 8))
(byte)(0xff & v)
```

The bytes written by this method may be read by the `readChar` method of interface `DataInput` , which will then return a `char` equal to `(char)v`.

Parameters:

`v - the char value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeInt

```
void writeInt(int v)
       throws IOException
```

Writes an `int` value, which is comprised of four bytes, to the output stream. The byte values to be written, in the order shown, are:

```
(byte)(0xff & (v >> 24))
(byte)(0xff & (v >> 16))
(byte)(0xff & (v >>  8))
(byte)(0xff & v)
```

The bytes written by this method may be read by the `readInt` method of interface `DataInput` , which will then return an `int` equal to `v`.

Parameters:

`v - the int value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeLong

```
void writeLong(long v)
        throws IOException
```

Writes a `long` value, which is comprised of eight bytes, to the output stream. The byte values to be written, in the order shown, are:

```
(byte)(0xff & (v >> 56))
(byte)(0xff & (v >> 48))
(byte)(0xff & (v >> 40))
(byte)(0xff & (v >> 32))
(byte)(0xff & (v >> 24))
(byte)(0xff & (v >> 16))
(byte)(0xff & (v >>  8))
(byte)(0xff & v)
```

The bytes written by this method may be read by the `readLong` method of interface `DataInput` , which will then return a `long` equal to `v`.

Parameters:

`v - the long value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeFloat

```
void writeFloat(float v)
         throws IOException
```

Writes a `float` value, which is comprised of four bytes, to the output stream. It does this as if it first converts this `float` value to an `int` in exactly the manner of the `Float.floatToIntBits` method and then writes the `int` value in exactly the manner of the `writeInt` method. The bytes written by this method may be read by the `readFloat` method of interface `DataInput`, which will then return a `float` equal to `v`.

Parameters:

`v - the float value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeDouble

```
void writeDouble(double v)
          throws IOException
```

Writes a `double` value, which is comprised of eight bytes, to the output stream. It does this as if it first converts this `double` value to a `long` in exactly the manner of the `Double.doubleToLongBits` method and then writes the `long` value in exactly the manner of the `writeLong` method. The bytes written by this method may be read by the `readDouble` method of interface `DataInput`, which will then return a `double` equal to `v`.

Parameters:

`v - the double value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeBytes

```
void writeBytes(String s)
         throws IOException
```

Writes a string to the output stream. For every character in the string `s`, taken in order, one byte is written to the output stream. If `s` is `null`, a `NullPointerException` is thrown.

If `s.length` is zero, then no bytes are written. Otherwise, the character `s[0]` is written first, then `s[1]`, and so on; the last character written is `s[s.length-1]`. For each character, one byte is written, the low-order byte, in exactly the manner of the `writeByte` method . The high-order eight bits of each character in the string are ignored.

Parameters:

`s - the string of bytes to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeChars

```
void writeChars(String s)
         throws IOException
```

Writes every character in the string `s`, to the output stream, in order, two bytes per character. If `s` is `null`, a `NullPointerException` is thrown. If `s.length` is zero, then no characters are written. Otherwise, the character `s[0]` is written first, then `s[1]`, and so on; the last character written is `s[s.length-1]`. For each character, two bytes are actually written, high-order byte first, in exactly the manner of the `writeChar` method.

Parameters:

`s - the string value to be written.`

Throws:

`IOException - if an I/O error occurs.`

writeUTF

```
void writeUTF(String s)
       throws IOException
```

Writes two bytes of length information to the output stream, followed by the modified UTF-8 representation of every character in the string `s`. If `s` is `null`, a `NullPointerException` is thrown. Each character in the string `s` is converted to a group of one, two, or three bytes, depending on the value of the character.

If a character `c` is in the range `\u0001` through `\u007f`, it is represented by one byte:

```
(byte)c
```

If a character `c` is `\u0000` or is in the range `\u0080` through `\u07ff`, then it is represented by two bytes, to be written in the order shown:

```
(byte)(0xc0 | (0x1f & (c >> 6)))
(byte)(0x80 | (0x3f & c))
```

If a character `c` is in the range `\u0800` through `uffff`, then it is represented by three bytes, to be written in the order shown:

```
(byte)(0xe0 | (0x0f & (c >> 12)))
(byte)(0x80 | (0x3f & (c >>  6)))
(byte)(0x80 | (0x3f & c))
```

First, the total number of bytes needed to represent all the characters of `s` is calculated. If this number is larger than `65535`, then a `UTFDataFormatException` is thrown. Otherwise, this length is written to the output stream in exactly the manner of the `writeShort` method; after this, the one-, two-, or three-byte representation of each character in the string `s` is written.

The bytes written by this method may be read by the `readUTF` method of interface `DataInput` , which will then return a `String` equal to `s`.

Parameters:

`s - the string value to be written.`

Throws:

`IOException - if an I/O error occurs.`

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.