JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class FileReader

java.lang.Object
    java.io.Reader
        java.io.InputStreamReader
            java.io.FileReader

All Implemented Interfaces:

Closeable, AutoCloseable, Readable

```
public class FileReader
extends InputStreamReader
```

Convenience class for reading character files. The constructors of this class assume that the default character encoding and the default byte-buffer size are appropriate. To specify these values yourself, construct an InputStreamReader on a FileInputStream.

FileReader is meant for reading streams of characters. For reading streams of raw bytes, consider using a FileInputStream.

Since:

JDK1.1

See Also:

InputStreamReader, FileInputStream

Field Summary

Fields inherited from class java.io.Reader

lock

Constructor Summary

Constructors

Constructor	Description
`FileReader(File file)`	Creates a new `FileReader`, given the `File` to read from.
`FileReader(FileDescriptor fd)`	Creates a new `FileReader`, given the `FileDescriptor` to read from.
`FileReader(String fileName)`	Creates a new `FileReader`, given the name of the file to read from.

Method Summary

Methods inherited from class java.io.InputStreamReader

`close`, `getEncoding`, `read`, `read`, `ready`

Methods inherited from class java.io.Reader

`mark`, `markSupported`, `read`, `read`, `reset`, `skip`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

FileReader

```
public FileReader(String fileName)
           throws FileNotFoundException
```

Creates a new `FileReader`, given the name of the file to read from.

Parameters:

`fileName - the name of the file to read from`

Throws:

FileNotFoundException - if the named file does not exist, is a directory rather than a regular file, or for some other reason cannot be opened for reading.

FileReader

```
public FileReader(File file)
           throws FileNotFoundException
```

Creates a new FileReader, given the File to read from.

Parameters:

file - the File to read from

Throws:

FileNotFoundException - if the file does not exist, is a directory rather than a regular file, or for some other reason cannot be opened for reading.

FileReader

```
public FileReader(FileDescriptor fd)
```

Creates a new FileReader, given the FileDescriptor to read from.

Parameters:

fd - the FileDescriptor to read from

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.