JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class FilterReader

java.lang.Object
    java.io.Reader
        java.io.FilterReader

All Implemented Interfaces:

`Closeable`, `AutoCloseable`, `Readable`

Direct Known Subclasses:

`PushbackReader`

```
public abstract class FilterReader
extends Reader
```

Abstract class for reading filtered character streams. The abstract class `FilterReader` itself provides default methods that pass all requests to the contained stream. Subclasses of `FilterReader` should override some of these methods and may also provide additional methods and fields.

Since:

`JDK1.1`

Field Summary

Fields

Modifier and Type	Field	Description
`protected Reader`	`in`	The underlying character-input stream.

Fields inherited from class java.io.Reader

`lock`

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	`FilterReader(Reader in)`	Creates a new filtered reader.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	`close()`	Closes the stream and releases any system resources associated with it.
void	`mark(int readAheadLimit)`	Marks the present position in the stream.
boolean	`markSupported()`	Tells whether this stream supports the mark() operation.
int	`read()`	Reads a single character.
int	`read(char[] cbuf, int off, int len)`	Reads characters into a portion of an array.
boolean	`ready()`	Tells whether this stream is ready to be read.
void	`reset()`	Resets the stream.
long	`skip(long n)`	Skips characters.

Methods inherited from class java.io.Reader

read, read

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

in

```
protected Reader in
```

The underlying character-input stream.

Constructor Detail

FilterReader

```
protected FilterReader(Reader in)
```

Creates a new filtered reader.

Parameters:

`in - a Reader object providing the underlying stream.`

Throws:

`NullPointerException - if in is null`

Method Detail

read

```
public int read()
         throws IOException
```

Reads a single character.

Overrides:

`read in class Reader`

Returns:

The character read, as an integer in the range 0 to 65535 (0x00-0xffff), or -1 if the end of the stream has been reached

Throws:

IOException - If an I/O error occurs

read

```
public int read(char[] cbuf,
                int off,
                int len)
         throws IOException
```

Reads characters into a portion of an array.

Specified by:

read in class Reader

Parameters:

cbuf - Destination buffer

off - Offset at which to start storing characters

len - Maximum number of characters to read

Returns:

The number of characters read, or -1 if the end of the stream has been reached

Throws:

IOException - If an I/O error occurs

skip

```
public long skip(long n)
          throws IOException
```

Skips characters.

Overrides:

`skip` in class `Reader`

Parameters:

`n - The number of characters to skip`

Returns:

`The number of characters actually skipped`

Throws:

`IOException - If an I/O error occurs`

ready

```
public boolean ready()
              throws IOException
```

Tells whether this stream is ready to be read.

Overrides:

`ready` in class `Reader`

Returns:

`True if the next read() is guaranteed not to block for input, false otherwise. Note that returning false does not guarantee that the next read will block.`

Throws:

`IOException - If an I/O error occurs`

markSupported

```
public boolean markSupported()
```

Tells whether this stream supports the mark() operation.

Overrides:

`markSupported` in class `Reader`

Returns:

`true if and only if this stream supports the mark operation.`

mark

```
public void mark(int readAheadLimit)
          throws IOException
```

Marks the present position in the stream.

Overrides:

`mark` in class `Reader`

Parameters:

`readAheadLimit - Limit on the number of characters that may be read while still preserving the mark. After reading this many characters, attempting to reset the stream may fail.`

Throws:

`IOException - If an I/O error occurs`

reset

```
public void reset()
           throws IOException
```

Resets the stream.

Overrides:

`reset` in class `Reader`

Throws:

`IOException - If an I/O error occurs`

close

```
public void close()
           throws IOException
```

Description copied from class: Reader

Closes the stream and releases any system resources associated with it. Once the stream has been closed, further read(), ready(), mark(), reset(), or skip() invocations will throw an IOException. Closing a previously closed stream has no effect.

Specified by:

`close` in interface `Closeable`

Specified by:

`close` in interface `AutoCloseable`

Specified by:

close in class Reader

Throws:

IOException - If an I/O error occurs

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.