JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class IOError

java.lang.Object
  java.lang.Throwable
    java.lang.Error
      java.io.IOError

All Implemented Interfaces:

Serializable

```
public class IOError
extends Error
```

Thrown when a serious I/O error has occurred.

Since:

1.6

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IOError(Throwable cause)`	Constructs a new instance of IOError with the specified cause.

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

IOError

```
public IOError(Throwable cause)
```

Constructs a new instance of IOError with the specified cause. The IOError is created with the detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of cause).

Parameters:

`cause - The cause of this error, or null if the cause is not known`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.