JavaScript is disabled on your browser.



compact1, compact2, compact3

java.io

# Class InvalidClassException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.io.IOException
        java.io.ObjectStreamException
          java.io.InvalidClassException

**All Implemented Interfaces:**

Serializable

---

```
public class InvalidClassException
extends ObjectStreamException
```

Thrown when the Serialization runtime detects one of the following problems with a Class.

- The serial version of the class does not match that of the class descriptor read from the stream
- The class contains unknown datatypes
- The class does not have an accessible no-arg constructor

**Since:**

JDK1.1

**See Also:**

Serialized Form

## *Field Summary*

**Fields**

| Modifier and Type | Field | Description |
|---|---|---|

| | | |
|---|---|---|
| String | classname | Name of the invalid class. |

### Constructor Summary

**Constructors**

| Constructor | Description |
|---|---|
| InvalidClassException(String reason) | Report an InvalidClassException for the reason specified. |
| InvalidClassException(String cname, String reason) | Constructs an InvalidClassException object. |

### Method Summary

**Concrete Methods**

| Modifier and Type | Method | Description |
|---|---|---|
| String | getMessage() | Produce the message and include the classname, if present. |

#### Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

### Field Detail

#### classname

```
public String classname
```

Name of the invalid class.

## *Constructor Detail*

### InvalidClassException

```
public InvalidClassException(String reason)
```

Report an InvalidClassException for the reason specified.

**Parameters:**

`reason - String describing the reason for the exception.`

### InvalidClassException

```
public InvalidClassException(String cname,
                             String reason)
```

Constructs an InvalidClassException object.

**Parameters:**

`cname - a String naming the invalid class.`

`reason - a String describing the reason for the exception.`

## *Method Detail*

### getMessage

```
public String getMessage()
```

Produce the message and include the classname, if present.

**Overrides:**

`getMessage in class Throwable`

**Returns:**

C

```
the detail message string of this Throwable instance (which may be
null).
```




Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.