JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class LineNumberReader

java.lang.Object
    java.io.Reader
        java.io.BufferedReader
            java.io.LineNumberReader

All Implemented Interfaces:

`Closeable`, `AutoCloseable`, `Readable`

```
public class LineNumberReader
extends BufferedReader
```

A buffered character-input stream that keeps track of line numbers. This class defines methods `setLineNumber(int)` and `getLineNumber()` for setting and getting the current line number respectively.

By default, line numbering begins at 0. This number increments at every line terminator as the data is read, and can be changed with a call to `setLineNumber(int)`. Note however, that `setLineNumber(int)` does not actually change the current position in the stream; it only changes the value that will be returned by `getLineNumber()`.

A line is considered to be terminated by any one of a line feed ('\n'), a carriage return ('\r'), or a carriage return followed immediately by a linefeed.

Since:

`JDK1.1`

Field Summary

Fields inherited from class java.io.Reader

lock

Constructor Summary

Constructors

Constructor	Description
LineNumberReader(Reader in)	Create a new line-numbering reader, using the default input-buffer size.
LineNumberReader(Reader in, int sz)	Create a new line-numbering reader, reading characters into a buffer of the given size.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
int	getLineNumber()	Get the current line number.
void	mark(int readAheadLimit)	Mark the present position in the stream.
int	read()	Read a single character.
int	read(char[] cbuf, int off, int len)	Read characters into a portion of an array.
String	readLine()	Read a line of text.
void	reset()	Reset the stream to the most recent mark.
void	setLineNumber(int lineNumber)	Set the current line number.

long	**skip**(long n)	Skip characters.

Methods inherited from class java.io.BufferedReader

close, lines, markSupported, ready

Methods inherited from class java.io.Reader

read, read

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

LineNumberReader

```
public LineNumberReader(Reader in)
```

Create a new line-numbering reader, using the default input-buffer size.

Parameters:

in - A Reader object to provide the underlying stream

LineNumberReader

```
public LineNumberReader(Reader in,
                        int sz)
```

Create a new line-numbering reader, reading characters into a buffer of the given size.

Parameters:

in - A Reader object to provide the underlying stream

sz - An int specifying the size of the buffer

Method Detail

setLineNumber

```
public void setLineNumber(int lineNumber)
```

Set the current line number.

Parameters:

`lineNumber - An int specifying the line number`

See Also:

`getLineNumber()`

getLineNumber

```
public int getLineNumber()
```

Get the current line number.

Returns:

`The current line number`

See Also:

`setLineNumber(int)`

read

```
public int read()
         throws IOException
```

Read a single character. Line terminators are compressed into single newline ('\n') characters. Whenever a line terminator is read the current line number is incremented.

Overrides:

`read in class BufferedReader`

Returns:

`The character read, or -1 if the end of the stream has been reached`

Throws:

`IOException - If an I/O error occurs`

read

```
public int read(char[] cbuf,
                int off,
                int len)
         throws IOException
```

Read characters into a portion of an array. Whenever a line terminator is read the current line number is incremented.

Overrides:

`read` in class `BufferedReader`

Parameters:

`cbuf - Destination buffer`

`off - Offset at which to start storing characters`

`len - Maximum number of characters to read`

Returns:

`The number of bytes read, or -1 if the end of the stream has already been reached`

Throws:

`IOException - If an I/O error occurs`

readLine

```
public String readLine()
                throws IOException
```

Read a line of text. Whenever a line terminator is read the current line number is incremented.

Overrides:

`readLine` in class `BufferedReader`

Returns:

`A String containing the contents of the line, not including any line termination characters, or null if the end of the stream has been reached`

Throws:

`IOException - If an I/O error occurs`

See Also:

`Files.readAllLines(java.nio.file.Path, java.nio.charset.Charset)`

skip

```
public long skip(long n)
          throws IOException
```

Skip characters.

Overrides:

`skip` in class `BufferedReader`

Parameters:

`n - The number of characters to skip`

Returns:

`The number of characters actually skipped`

Throws:

`IOException - If an I/O error occurs`

`IllegalArgumentException - If n is negative`

mark

```
public void mark(int readAheadLimit)
          throws IOException
```

Mark the present position in the stream. Subsequent calls to reset() will attempt to reposition the stream to this point, and will also reset the line number appropriately.

Overrides:

`mark` in class `BufferedReader`

Parameters:

`readAheadLimit - Limit on the number of characters that may be read while still preserving the mark. After reading this many characters, attempting to reset the stream may fail.`

Throws:

`IOException - If an I/O error occurs`

reset

```
public void reset()
           throws IOException
```

Reset the stream to the most recent mark.

Overrides:

`reset` in class `BufferedReader`

Throws:

`IOException` - If the stream has not been marked, or if the mark has been invalidated

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.