JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class NotActiveException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.io.IOException
        java.io.ObjectStreamException
          java.io.NotActiveException

All Implemented Interfaces:

Serializable

```
public class NotActiveException
extends ObjectStreamException
```

Thrown when serialization or deserialization is not active.

Since:

JDK1.1

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`NotActiveException()`	Constructor to create a new NotActiveException without a reason.
`NotActiveException(String reason)`	

	Constructor to create a new NotActiveException with the reason given.

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

NotActiveException

```
public NotActiveException(String reason)
```

Constructor to create a new NotActiveException with the reason given.

Parameters:

`reason - a String describing the reason for the exception.`

NotActiveException

```
public NotActiveException()
```

Constructor to create a new NotActiveException without a reason.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.