JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class ObjectInputStream.GetField

java.lang.Object
    java.io.ObjectInputStream.GetField

Enclosing class:

ObjectInputStream

```
public abstract static class ObjectInputStream.GetField
extends Object
```

Provide access to the persistent fields read from the input stream.

Constructor Summary

Constructors

Constructor	Description
GetField()	

Method Summary

Abstract Methods

Modifier and Type	Method	Description

abstract boolean	**defaulted**(**String** name)	Return true if the named field is defaulted and has no value in this stream.
abstract boolean	**get**(**String** name, boolean val)	Get the value of the named boolean field from the persistent field.
abstract byte	**get**(**String** name, byte val)	Get the value of the named byte field from the persistent field.
abstract char	**get**(**String** name, char val)	Get the value of the named char field from the persistent field.
abstract double	**get**(**String** name, double val)	Get the value of the named double field from the persistent field.
abstract float	**get**(**String** name, float val)	Get the value of the named float field from the persistent field.
abstract int	**get**(**String** name, int val)	Get the value of the named int field from the persistent field.
abstract long	**get**(**String** name, long val)	Get the value of the named long field from the persistent field.
abstract **Object**	**get**(**String** name, **Object** val)	Get the value of the named Object field from the persistent field.
abstract short	**get**(**String** name, short val)	Get the value of the named short

		field from the persistent field.
abstract **ObjectStreamClass**	**getObjectStreamClass**()	Get the ObjectStreamClass that describes the fields in the stream.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

GetField

```
public GetField()
```

Method Detail

getObjectStreamClass

```
public abstract ObjectStreamClass getObjectStreamClass()
```

Get the ObjectStreamClass that describes the fields in the stream.

Returns:

the descriptor class that describes the serializable fields

defaulted

```
public abstract boolean defaulted(String name)
                           throws IOException
```

Return true if the named field is defaulted and has no value in this stream.

Parameters:

name - the name of the field

Returns:

true, if and only if the named field is defaulted

Throws:

IOException - if there are I/O errors while reading from the underlying InputStream

IllegalArgumentException - if name does not correspond to a serializable field

get

```
public abstract boolean get(String name,
                            boolean val)
                     throws IOException
```

Get the value of the named boolean field from the persistent field.

Parameters:

name - the name of the field

val - the default value to use if name does not have a value

Returns:

the value of the named boolean field

Throws:

IOException - if there are I/O errors while reading from the underlying InputStream

IllegalArgumentException - if type of name is not serializable or if the field type is incorrect

get

```
public abstract byte get(String name,
                         byte val)
                  throws IOException
```

Get the value of the named byte field from the persistent field.

Parameters:

name - the name of the field

val - the default value to use if name does not have a value

Returns:

the value of the named byte field

Throws:

IOException - if there are I/O errors while reading from the underlying InputStream

IllegalArgumentException - if type of name is not serializable or if the field type is incorrect

get

```
public abstract char get(String name,
                         char val)
                  throws IOException
```

Get the value of the named char field from the persistent field.

Parameters:

name - the name of the field

val - the default value to use if name does not have a value

Returns:

the value of the named char field

Throws:

IOException - if there are I/O errors while reading from the underlying InputStream

IllegalArgumentException - if type of name is not serializable or if the field type is incorrect

get

```
public abstract short get(String name,
                          short val)
                   throws IOException
```

Get the value of the named short field from the persistent field.

Parameters:

name - the name of the field

val - the default value to use if name does not have a value

Returns:

the value of the named short field

Throws:

IOException - if there are I/O errors while reading from the underlying InputStream

IllegalArgumentException - if type of name is not serializable or if the field type is incorrect

get

```
public abstract int get(String name,
                        int val)
                 throws IOException
```

Get the value of the named int field from the persistent field.

Parameters:

`name - the name of the field`

`val - the default value to use if name does not have a value`

Returns:

`the value of the named int field`

Throws:

`IOException - if there are I/O errors while reading from the underlying InputStream`

`IllegalArgumentException - if type of name is not serializable or if the field type is incorrect`

get

```
public abstract long get(String name,
                         long val)
                  throws IOException
```

Get the value of the named long field from the persistent field.

Parameters:

`name - the name of the field`

`val - the default value to use if name does not have a value`

Returns:

`the value of the named long field`

Throws:

`IOException - if there are I/O errors while reading from the underlying InputStream`

`IllegalArgumentException - if type of name is not serializable or if the field type is incorrect`

get

```
public abstract float get(String name,
                          float val)
                   throws IOException
```

Get the value of the named float field from the persistent field.

Parameters:

`name - the name of the field`

`val - the default value to use if name does not have a value`

Returns:

`the value of the named float field`

Throws:

`IOException - if there are I/O errors while reading from the underlying InputStream`

`IllegalArgumentException - if type of name is not serializable or if the field type is incorrect`

get

```
public abstract double get(String name,
                           double val)
                    throws IOException
```

Get the value of the named double field from the persistent field.

Parameters:

`name - the name of the field`

`val - the default value to use if name does not have a value`

Returns:

`the value of the named double field`

Throws:

`IOException - if there are I/O errors while reading from the underlying InputStream`

`IllegalArgumentException - if type of name is not serializable or if the field type is incorrect`

get

```
public abstract Object get(String name,
                           Object val)
                    throws IOException
```

Get the value of the named Object field from the persistent field.

Parameters:

`name - the name of the field`

`val - the default value to use if name does not have a value`

Returns:

`the value of the named Object field`

Throws:

`IOException - if there are I/O errors while reading from the underlying InputStream`

`IllegalArgumentException - if type of name is not serializable or if the field type is incorrect`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.