JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Interface ObjectOutput

All Superinterfaces:

AutoCloseable, DataOutput

All Known Implementing Classes:

ObjectOutputStream

```
public interface ObjectOutput
extends DataOutput, AutoCloseable
```

ObjectOutput extends the DataOutput interface to include writing of objects. DataOutput includes methods for output of primitive types, ObjectOutput extends that interface to include objects, arrays, and Strings.

Since:

JDK1.1

See Also:

InputStream, ObjectOutputStream, ObjectInputStream

Method Summary

Abstract Methods

Modifier and Type	Method	Description
void	close()	Closes the stream.
void	flush()	Flushes the stream.
void	write(byte[] b)	Writes an array of bytes.

void	**write**(byte[] b, int off, int len)	Writes a sub array of bytes.
void	**write**(int b)	Writes a byte.
void	**writeObject**(**Object** obj)	Write an object to the underlying storage or stream.

Methods inherited from interface java.io.DataOutput

writeBoolean, writeByte, writeBytes, writeChar, writeChars, writeDouble, writeFloat, writeInt, writeLong, writeShort, writeUTF

Method Detail

writeObject

```
void writeObject(Object obj)
          throws IOException
```

Write an object to the underlying storage or stream. The class that implements this interface defines how the object is written.

Parameters:

obj - the object to be written

Throws:

IOException - Any of the usual Input/Output related exceptions.

write

```
void write(int b)
    throws IOException
```

Writes a byte. This method will block until the byte is actually written.

Specified by:

write in interface DataOutput

Parameters:

b - the byte

Throws:

IOException - If an I/O error has occurred.

write

```
void write(byte[] b)
    throws IOException
```

Writes an array of bytes. This method will block until the bytes are actually written.

Specified by:

`write` in interface `DataOutput`

Parameters:

`b - the data to be written`

Throws:

`IOException - If an I/O error has occurred.`

write

```
void write(byte[] b,
           int off,
           int len)
    throws IOException
```

Writes a sub array of bytes.

Specified by:

`write` in interface `DataOutput`

Parameters:

`b - the data to be written`

`off - the start offset in the data`

`len - the number of bytes that are written`

Throws:

`IOException - If an I/O error has occurred.`

flush

```
void flush()
    throws IOException
```

Flushes the stream. This will write any buffered output bytes.

Throws:

`IOException - If an I/O error has occurred.`

close

```
void close()
    throws IOException
```

Closes the stream. This method must be called to release any resources associated with the stream.

Specified by:

`close` in interface `AutoCloseable`

Throws:

`IOException` - If an I/O error has occurred.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.