JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class ObjectOutputStream.PutField

java.lang.Object
    java.io.ObjectOutputStream.PutField

Enclosing class:

ObjectOutputStream

```
public abstract static class ObjectOutputStream.PutField
extends Object
```

Provide programmatic access to the persistent fields to be written to ObjectOutput.

Since:

1.2

Constructor Summary

Constructors

Constructor	Description
PutField()	

Method Summary

Deprecated Methods

Modifier and Type	Method	Description
abstract void		

	put(**String** name, boolean val)	Put the value of the named boolean field into the persistent field.
abstract void	**put**(**String** name, byte val)	Put the value of the named byte field into the persistent field.
abstract void	**put**(**String** name, char val)	Put the value of the named char field into the persistent field.
abstract void	**put**(**String** name, double val)	Put the value of the named double field into the persistent field.
abstract void	**put**(**String** name, float val)	Put the value of the named float field into the persistent field.
abstract void	**put**(**String** name, int val)	Put the value of the named int field into the persistent field.
abstract void	**put**(**String** name, long val)	Put the value of the named long field into the persistent field.
abstract void	**put**(**String** name, **Object** val)	Put the value of the named Object field into the persistent field.
abstract void	**put**(**String** name, short val)	Put the value of the named short field into the persistent field.
abstract void	**write**(**ObjectOutput** out)	**Deprecated.** This method does not write the values contained by this `PutField` object in a proper format, and may result in corruption of the serialization stream. The correct way to write `PutField` data is by calling the **`ObjectOutputStream.writeFields()`** method.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

PutField

```
public PutField()
```

Method Detail

put

```
public abstract void put(String name,
                         boolean val)
```

Put the value of the named boolean field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not boolean`

put

```
public abstract void put(String name,
                         byte val)
```

Put the value of the named byte field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not byte`

put

```
public abstract void put(String name,
                         char val)
```

Put the value of the named char field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not char`

put

```
public abstract void put(String name,
                         short val)
```

Put the value of the named short field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not short`

put

```
public abstract void put(String name,
                         int val)
```

Put the value of the named int field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not int`

put

```
public abstract void put(String name,
                         long val)
```

Put the value of the named long field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not long`

put

```
public abstract void put(String name,
                         float val)
```

Put the value of the named float field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not float`

put

```
public abstract void put(String name,
                         double val)
```

Put the value of the named double field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not double`

put

```
public abstract void put(String name,
                         Object val)
```

Put the value of the named Object field into the persistent field.

Parameters:

`name - the name of the serializable field`

`val - the value to assign to the field (which may be null)`

Throws:

`IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not a reference type`

write

```
@Deprecated
public abstract void write(ObjectOutput out)
                                throws IOException
```

Deprecated. *This method does not write the values contained by this `PutField` object in a proper format, and may result in corruption of the serialization stream. The correct way to write `PutField` data is by calling the `ObjectOutputStream.writeFields()` method.*

Write the data and fields to the specified ObjectOutput stream, which must be the same stream that produced this `PutField` object.

Parameters:

`out - the stream to write the data and fields to`

Throws:

`IOException - if I/O errors occur while writing to the underlying stream`

`IllegalArgumentException` - if the specified stream is not the same stream that produced this PutField object

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.