JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class PipedWriter

java.lang.Object
    java.io.Writer
        java.io.PipedWriter

All Implemented Interfaces:

`Closeable`, `Flushable`, `Appendable`, `AutoCloseable`

```
public class PipedWriter
extends Writer
```

Piped character-output streams.

Since:

JDK1.1

Field Summary

Fields inherited from class java.io.Writer

`lock`

Constructor Summary

Constructors

Constructor	Description
`PipedWriter()`	Creates a piped writer that is not yet connected to a piped reader.

PipedWriter(**PipedReader** snk)	Creates a piped writer connected to the specified piped reader.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	**close**()	Closes this piped output stream and releases any system resources associated with this stream.
void	**connect**(**PipedReader** snk)	Connects this piped writer to a receiver.
void	**flush**()	Flushes this output stream and forces any buffered output characters to be written out.
void	**write**(char[] cbuf, int off, int len)	Writes `len` characters from the specified character array starting at offset `off` to this piped output stream.
void	**write**(int c)	Writes the specified `char` to the piped output stream.

Methods inherited from class java.io.Writer

append, append, append, write, write, write

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

PipedWriter

```
public PipedWriter(PipedReader snk)
            throws IOException
```

Creates a piped writer connected to the specified piped reader. Data characters written to this stream will then be available as input from `snk`.

Parameters:

`snk - The piped reader to connect to.`

Throws:

`IOException - if an I/O error occurs.`

PipedWriter

```
public PipedWriter()
```

Creates a piped writer that is not yet connected to a piped reader. It must be connected to a piped reader, either by the receiver or the sender, before being used.

See Also:

`PipedReader.connect(java.io.PipedWriter)`, `connect(java.io.PipedReader)`

Method Detail

connect

```
public void connect(PipedReader snk)
             throws IOException
```

Connects this piped writer to a receiver. If this object is already connected to some other piped reader, an `IOException` is thrown.

If `snk` is an unconnected piped reader and `src` is an unconnected piped writer, they may be connected by either the call:

```
src.connect(snk)
```

or the call:

```
snk.connect(src)
```

The two calls have the same effect.

Parameters:

`snk - the piped reader to connect to.`

Throws:

`IOException - if an I/O error occurs.`

write

```
public void write(int c)
           throws IOException
```

Writes the specified `char` to the piped output stream. If a thread was reading data characters from the connected piped input stream, but the thread is no longer alive, then an `IOException` is thrown.

Implements the `write` method of `Writer`.

Overrides:

`write in class Writer`

Parameters:

`c - the char to be written.`

Throws:

`IOException - if the pipe is broken, unconnected, closed or an I/O error occurs.`

write

```
public void write(char[] cbuf,
                  int off,
                  int len)
           throws IOException
```

Writes `len` characters from the specified character array starting at offset `off` to this piped output stream. This method blocks until all the characters are written to the output stream. If a thread was reading data characters from the connected piped input stream, but the thread is no longer alive, then an `IOException` is thrown.

Specified by:

`write in class Writer`

Parameters:

`cbuf - the data.`

`off - the start offset in the data.`

len - the number of characters to write.

Throws:

IOException - if the pipe is broken, unconnected, closed or an I/O error occurs.

flush

```
public void flush()
           throws IOException
```

Flushes this output stream and forces any buffered output characters to be written out. This will notify any readers that characters are waiting in the pipe.

Specified by:

flush in interface Flushable

Specified by:

flush in class Writer

Throws:

IOException - if the pipe is closed, or an I/O error occurs.

close

```
public void close()
           throws IOException
```

Closes this piped output stream and releases any system resources associated with this stream. This stream may no longer be used for writing characters.

Specified by:

close in interface Closeable

Specified by:

close in interface AutoCloseable

Specified by:

close in class Writer

Throws:

C

`IOException` - if an I/O error occurs.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.