JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class StringBufferInputStream

java.lang.Object
    java.io.InputStream
        java.io.StringBufferInputStream

All Implemented Interfaces:

`Closeable, AutoCloseable`

Deprecated.
This class does not properly convert characters into bytes. As of JDK 1.1, the preferred way to create a stream from a string is via the `StringReader` class.

```
@Deprecated
public class StringBufferInputStream
extends InputStream
```

This class allows an application to create an input stream in which the bytes read are supplied by the contents of a string. Applications can also read bytes from a byte array by using a `ByteArrayInputStream`.

Only the low eight bits of each character in the string are used by this class.

Since:

`JDK1.0`

See Also:

`ByteArrayInputStream, StringReader`

Field Summary

Fields

Modifier and Type	Field	Description

protected String	buffer	**Deprecated.** The string from which bytes are read.
protected int	count	**Deprecated.** The number of valid characters in the input stream buffer.
protected int	pos	**Deprecated.** The index of the next character to read from the input stream buffer.

Constructor Summary

Constructors

Constructor	Description
StringBufferInputStream(String s)	**Deprecated.** Creates a string input stream to read data from the specified string.

Method Summary

Concrete Methods

Deprecated Methods

Modifier and Type	Method	Description
int	available()	**Deprecated.** Returns the number of bytes that can be read from the input stream without blocking.
int	read()	**Deprecated.** Reads the next byte of data from this input stream.
int	read(byte[] b, int off, int len)	**Deprecated.** Reads up to len bytes of data from this input stream into an array of bytes.
void	reset()	**Deprecated.**

		Resets the input stream to begin reading from the first character of this input stream's underlying buffer.
long	**skip**(long n)	**Deprecated.** Skips n bytes of input from this input stream.

Methods inherited from class java.io.InputStream

close, mark, markSupported, read

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

buffer

```
protected String buffer
```

Deprecated.
The string from which bytes are read.

pos

```
protected int pos
```

Deprecated.
The index of the next character to read from the input stream buffer.

See Also:
buffer

count

```
protected int count
```

Deprecated.
The number of valid characters in the input stream buffer.

See Also:

`buffer`

Constructor Detail

StringBufferInputStream

```
public StringBufferInputStream(String s)
```

Deprecated.

Creates a string input stream to read data from the specified string.

Parameters:

`s - the underlying input buffer.`

Method Detail

read

```
public int read()
```

Deprecated.

Reads the next byte of data from this input stream. The value byte is returned as an `int` in the range `0` to `255`. If no byte is available because the end of the stream has been reached, the value `-1` is returned.

The `read` method of `StringBufferInputStream` cannot block. It returns the low eight bits of the next character in this input stream's buffer.

Specified by:

`read` in class `InputStream`

Returns:

`the next byte of data, or -1 if the end of the stream is reached.`

read

```
public int read(byte[] b,
                int off,
                int len)
```

Deprecated.

Reads up to `len` bytes of data from this input stream into an array of bytes.

The read method of StringBufferInputStream cannot block. It copies the low eight bits from the characters in this input stream's buffer into the byte array argument.

Overrides:

read in class InputStream

Parameters:

b - the buffer into which the data is read.

off - the start offset of the data.

len - the maximum number of bytes read.

Returns:

the total number of bytes read into the buffer, or -1 if there is no more data because the end of the stream has been reached.

See Also:

InputStream.read()

skip

public long skip(long n)

Deprecated.

Skips n bytes of input from this input stream. Fewer bytes might be skipped if the end of the input stream is reached.

Overrides:

skip in class InputStream

Parameters:

n - the number of bytes to be skipped.

Returns:

the actual number of bytes skipped.

available

public int available()

Deprecated.

Returns the number of bytes that can be read from the input stream without blocking.

Overrides:

available in class InputStream

Returns:

the value of count - pos, which is the number of bytes remaining to be read from the input buffer.

reset

```
public void reset()
```

Deprecated.

Resets the input stream to begin reading from the first character of this input stream's underlying buffer.

Overrides:

`reset` in class `InputStream`

See Also:

`InputStream.mark(int)`, `IOException`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.