JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class WriteAbortedException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.io.IOException
        java.io.ObjectStreamException
          java.io.WriteAbortedException

All Implemented Interfaces:

Serializable

```
public class WriteAbortedException
extends ObjectStreamException
```

Signals that one of the ObjectStreamExceptions was thrown during a write operation. Thrown during a read operation when one of the ObjectStreamExceptions was thrown during a write operation. The exception that terminated the write can be found in the detail field. The stream is reset to it's initial state and all references to objects already deserialized are discarded.

As of release 1.4, this exception has been retrofitted to conform to the general purpose exception-chaining mechanism. The "exception causing the abort" that is provided at construction time and accessed via the public `detail` field is now known as the *cause*, and may be accessed via the `Throwable.getCause()` method, as well as the aforementioned "legacy field."

Since:

JDK1.1

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
`Exception`	`detail`	Exception that was caught while writing the ObjectStream.

Constructor Summary

Constructors

Constructor	Description
`WriteAbortedException(String s, Exception ex)`	Constructs a WriteAbortedException with a string describing the exception and the exception causing the abort.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`Throwable`	`getCause()`	Returns the exception that terminated the operation (the *cause*).
`String`	`getMessage()`	Produce the message and include the message from the nested exception, if there is one.

Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getLocalizedMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Field Detail

detail

```
public Exception detail
```

Exception that was caught while writing the ObjectStream.

This field predates the general-purpose exception chaining facility. The Throwable.getCause() method is now the preferred means of obtaining this information.

Constructor Detail

WriteAbortedException

```
public WriteAbortedException(String s,
                             Exception ex)
```

Constructs a WriteAbortedException with a string describing the exception and the exception causing the abort.

Parameters:

`s - String describing the exception.`

`ex - Exception causing the abort.`

Method Detail

getMessage

```
public String getMessage()
```

Produce the message and include the message from the nested exception, if there is one.

Overrides:

getMessage in class Throwable

Returns:

the detail message string of this Throwable instance (which may be null).

getCause

public Throwable getCause()

Returns the exception that terminated the operation (the *cause*).

Overrides:

getCause in class Throwable

Returns:

the exception that terminated the operation (the *cause*), which may be null.

Since:

1.4

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.