JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Class Character.Subset

java.lang.Object
    java.lang.Character.Subset

Direct Known Subclasses:

Character.UnicodeBlock, InputSubset

Enclosing class:

Character

```
public static class Character.Subset
extends Object
```

Instances of this class represent particular subsets of the Unicode character set. The only family of subsets defined in the Character class is Character.UnicodeBlock. Other portions of the Java API may define other subsets for their own purposes.

Since:

1.2

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	Subset(String name)	Constructs a new Subset instance.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	**equals**(**Object** obj)	Compares two Subset objects for equality.
int	**hashCode**()	Returns the standard hash code as defined by the **Object.hashCode()** method.
String	**toString**()	Returns the name of this subset.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Constructor Detail

Subset

```
protected Subset(String name)
```

Constructs a new Subset instance.

Parameters:

name - The name of this subset

Throws:

NullPointerException - if name is null

Method Detail

equals

```
public final boolean equals(Object obj)
```

Compares two Subset objects for equality. This method returns true if and only if this and the argument refer to the same object; since this method is final, this guarantee holds for all subclasses.

Overrides:

equals in class Object

Parameters:

`obj - the reference object with which to compare.`

Returns:

`true if this object is the same as the obj argument; false otherwise.`

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public final int hashCode()
```

Returns the standard hash code as defined by the `Object.hashCode()` method. This method is `final` in order to ensure that the `equals` and `hashCode` methods will be consistent in all subclasses.

Overrides:

`hashCode` in class `Object`

Returns:

`a hash code value for this object.`

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

toString

```
public final String toString()
```

Returns the name of this subset.

Overrides:

`toString` in class `Object`

Returns:

```
a string representation of the object.
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.