JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Class Compiler

java.lang.Object
    java.lang.Compiler

```
public final class Compiler
extends Object
```

The `Compiler` class is provided to support Java-to-native-code compilers and related services. By design, the `Compiler` class does nothing; it serves as a placeholder for a JIT compiler implementation.

When the Java Virtual Machine first starts, it determines if the system property `java.compiler` exists. (System properties are accessible through `System.getProperty(String)` and `System.getProperty(String, String)`. If so, it is assumed to be the name of a library (with a platform-dependent exact location and type); `System.loadLibrary(java.lang.String)` is called to load that library. If this loading succeeds, the function named `java_lang_Compiler_start()` in that library is called.

If no compiler is available, these methods do nothing.

Since:

`JDK1.0`

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`static Object`	`command(Object any)`	Examines the argument type and

		its fields and perform some documented operation.
static boolean	**compileClass**(**Class**<?> clazz)	Compiles the specified class.
static boolean	**compileClasses**(**String** string)	Compiles all classes whose name matches the specified string.
static void	**disable**()	Cause the Compiler to cease operation.
static void	**enable**()	Cause the Compiler to resume operation.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

compileClass

```
public static boolean compileClass(Class<?> clazz)
```

Compiles the specified class.

Parameters:

clazz - A class

Returns:

true if the compilation succeeded; false if the compilation failed or no compiler is available

Throws:

NullPointerException - If clazz is null

compileClasses

```
public static boolean compileClasses(String string)
```

Compiles all classes whose name matches the specified string.

Parameters:

`string - The name of the classes to compile`

Returns:

`true if the compilation succeeded; false if the compilation failed or no compiler is available`

Throws:

`NullPointerException - If string is null`

command

```
public static Object command(Object any)
```

Examines the argument type and its fields and perform some documented operation. No specific operations are required.

Parameters:

`any - An argument`

Returns:

`A compiler-specific value, or null if no compiler is available`

Throws:

`NullPointerException - If any is null`

enable

```
public static void enable()
```

Cause the Compiler to resume operation.

disable

```
public static void disable()
```

Cause the Compiler to cease operation.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.