JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Class TypeNotPresentException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.TypeNotPresentException

All Implemented Interfaces:

Serializable

```
public class TypeNotPresentException
extends RuntimeException
```

Thrown when an application tries to access a type using a string representing the type's name, but no definition for the type with the specified name can be found. This exception differs from `ClassNotFoundException` in that `ClassNotFoundException` is a checked exception, whereas this exception is unchecked.

Note that this exception may be used when undefined type variables are accessed as well as when types (e.g., classes, interfaces or annotation types) are loaded. In particular, this exception can be thrown by the API used to read annotations reflectively.

Since:

1.5

See Also:

`AnnotatedElement`, `Serialized Form`

Constructor Summary

Constructors

Constructor	Description
`TypeNotPresentException(String typeName, Throwable cause)`	Constructs a TypeNotPresentExceptio for the named type with the specified cause.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`String`	`typeName()`	Returns the fully qualified name of the unavailable type.

Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Detail

TypeNotPresentException

```
public TypeNotPresentException(String typeName,
                               Throwable cause)
```

Constructs a `TypeNotPresentException` for the named type with the specified cause.

Parameters:

`typeName` - the fully qualified name of the unavailable type

cause - the exception that was thrown when the system attempted to load the named type, or null if unavailable or inapplicable

Method Detail

typeName

```
public String typeName()
```

Returns the fully qualified name of the unavailable type.

Returns:

the fully qualified name of the unavailable type

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.