JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Class VirtualMachineError

java.lang.Object
  java.lang.Throwable
    java.lang.Error
      java.lang.VirtualMachineError

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

InternalError, OutOfMemoryError, StackOverflowError, UnknownError

---

```
public abstract class VirtualMachineError
extends Error
```

Thrown to indicate that the Java Virtual Machine is broken or has run out of resources necessary for it to continue operating.

Since:

JDK1.0

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
VirtualMachineError()	Constructs a VirtualMachineError

	with no detail message.
`VirtualMachineError(String message)`	Constructs a `VirtualMachineError` with the specified detail message.
`VirtualMachineError(String message, Throwable cause)`	Constructs a `VirtualMachineError` with the specified detail message and cause.
`VirtualMachineError(Throwable cause)`	Constructs an a `VirtualMachineError` with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Method Summary

Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Detail

VirtualMachineError

```
public VirtualMachineError()
```

Constructs a `VirtualMachineError` with no detail message.

VirtualMachineError

```
public VirtualMachineError(String message)
```

Constructs a `VirtualMachineError` with the specified detail message.

Parameters:

`message - the detail message.`

VirtualMachineError

```
public VirtualMachineError(String message,
                           Throwable cause)
```

Constructs a `VirtualMachineError` with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this error's detail message.

Parameters:

`message - the detail message (which is saved for later retrieval by the Throwable.getMessage() method).`

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

Since:

`1.8`

VirtualMachineError

```
public VirtualMachineError(Throwable cause)
```

Constructs an a `VirtualMachineError` with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Parameters:

cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.8

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.