JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang.annotation

Interface Annotation

All Known Implementing Classes:

Action, Addressing, BindingType, ConstructorProperties, Deprecated, DescriptorKey, Documented, FaultAction, FunctionalInterface, Generated, HandlerChain, Inherited, InitParam, MTOM, MXBean, Native, Oneway, Override, PostConstruct, PreDestroy, Repeatable, RequestWrapper, Resource, Resources, RespectBinding, ResponseWrapper, Retention, SafeVarargs, ServiceMode, SOAPBinding, SOAPMessageHandler, SOAPMessageHandlers, SupportedAnnotationTypes, SupportedOptions, SupportedSourceVersion, SuppressWarnings, Target, Transient, WebEndpoint, WebFault, WebMethod, WebParam, WebResult, WebService, WebServiceClient, WebServiceFeatureAnnotation, WebServiceProvider, WebServiceRef, WebServiceRefs, XmlAccessorOrder, XmlAccessorType, XmlAnyAttribute, XmlAnyElement, XmlAttachmentRef, XmlAttribute, XmlElement, XmlElementDecl, XmlElementRef, XmlElementRefs, XmlElements, XmlElementWrapper, XmlEnum, XmlEnumValue, XmlID, XmlIDREF, XmlInlineBinaryData, XmlJavaTypeAdapter, XmlJavaTypeAdapters, XmlList, XmlMimeType, XmlMixed, XmlNs, XmlRegistry, XmlRootElement, XmlSchema, XmlSchemaType, XmlSchemaTypes, XmlSeeAlso, XmlTransient, XmlType, XmlValue

---

```
public interface Annotation
```

The common interface extended by all annotation types. Note that an interface that manually extends this one does *not* define an annotation type. Also note that this interface does not itself define an annotation type. More information about annotation types can be found in section 9.6 of *The Java™ Language Specification*. The AnnotatedElement interface discusses compatibility concerns when evolving an annotation type from being non-repeatable to being repeatable.

Since:

1.5

Method Summary

Abstract Methods

Modifier and Type	Method	Description
`Class<? extends Annotation>`	`annotationType()`	Returns the annotation type of this annotation.
`boolean`	`equals(Object obj)`	Returns true if the specified object represents an annotation that is logically equivalent to this one.
`int`	`hashCode()`	Returns the hash code of this annotation, as defined below:
`String`	`toString()`	Returns a string representation of this annotation.

Method Detail

equals

```
boolean equals(Object obj)
```

Returns true if the specified object represents an annotation that is logically equivalent to this one. In other words, returns true if the specified object is an instance of the same annotation type as this instance, all of whose members are equal to the corresponding member of this annotation, as defined below:

- Two corresponding primitive typed members whose values are `x` and `y` are considered equal if `x == y`, unless their type is `float` or `double`.
- Two corresponding `float` members whose values are `x` and `y` are considered equal if `Float.valueOf(x).equals(Float.valueOf(y))`. (Unlike the == operator, NaN is considered equal to itself, and `0.0f` unequal to `-0.0f`.)
- Two corresponding `double` members whose values are `x` and `y` are considered equal if `Double.valueOf(x).equals(Double.valueOf(y))`.

(Unlike the == operator, NaN is considered equal to itself, and `0.0` unequal to `-0.0`.)

- Two corresponding `String`, `Class`, enum, or annotation typed members whose values are `x` and `y` are considered equal if `x.equals(y)`. (Note that this definition is recursive for annotation typed members.)
- Two corresponding array typed members `x` and `y` are considered equal if `Arrays.equals(x, y)`, for the appropriate overloading of `Arrays.equals(long[], long[])`.

Overrides:

`equals` in class `Object`

Parameters:

`obj - the reference object with which to compare.`

Returns:

`true if the specified object represents an annotation that is logically equivalent to this one, otherwise false`

See Also:

`Object.hashCode()`, `HashMap`

hashCode

`int hashCode()`

Returns the hash code of this annotation, as defined below:

The hash code of an annotation is the sum of the hash codes of its members (including those with default values), as defined below: The hash code of an annotation member is (127 times the hash code of the member-name as computed by `String.hashCode()`) XOR the hash code of the member-value, as defined below:

The hash code of a member-value depends on its type:

- The hash code of a primitive value *v* is equal to *WrapperType*`.valueOf(`*v*`).hashCode()`, where *WrapperType* is the wrapper type corresponding to the primitive type of *v* (`Byte`, `Character`, `Double`, `Float`, `Integer`, `Long`, `Short`, or `Boolean`).
- The hash code of a string, enum, class, or annotation member-value I *v* is computed as by calling *v*`.hashCode()`. (In the case of annotation member values, this is a recursive definition.)
- The hash code of an array member-value is computed by calling the appropriate overloading of `Arrays.hashCode` on the value. (There is one overloading for each primitive type, and one for object reference types.)

Overrides:

`hashCode` in class `Object`

Returns:

the hash code of this annotation

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

toString

`String toString()`

Returns a string representation of this annotation. The details of the representation are implementation-dependent, but the following may be regarded as typical:

```
@com.acme.util.Name(first=Alfred, middle=E., last=Neuman)
```

Overrides:

`toString` in class `Object`

Returns:

a string representation of this annotation

annotationType

`Class<? extends Annotation> annotationType()`

Returns the annotation type of this annotation.

Returns:

the annotation type of this annotation

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.