JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang.annotation

Class AnnotationFormatError

java.lang.Object
    java.lang.Throwable
        java.lang.Error
            java.lang.annotation.AnnotationFormatError

All Implemented Interfaces:

Serializable

```
public class AnnotationFormatError
extends Error
```

Thrown when the annotation parser attempts to read an annotation from a class file and determines that the annotation is malformed. This error can be thrown by the API used to read annotations reflectively.

Since:

1.5

See Also:

AnnotatedElement, Serialized Form

Constructor Summary

Constructors

Constructor	Description
`AnnotationFormatError(String message)`	Constructs a new `AnnotationFormatError` with the specified detail message.

AnnotationFormatError(**String** message, **Throwable** cause)	Constructs a new AnnotationFormatError with the specified detail message and cause.
AnnotationFormatError(**Throwable** cause)	Constructs a new AnnotationFormatError with the specified cause and a detail message of (cause == null ? null : cause.toString()) (which typically contains the class and detail message of cause).

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

AnnotationFormatError

```
public AnnotationFormatError(String message)
```

Constructs a new AnnotationFormatError with the specified detail message.

Parameters:

message - the detail message.

AnnotationFormatError

```
public AnnotationFormatError(String message,
                             Throwable cause)
```

Constructs a new `AnnotationFormatError` with the specified detail message and cause. Note that the detail message associated with `cause` is *not* automatically incorporated in this error's detail message.

Parameters:

`message - the detail message`

`cause - the cause (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

AnnotationFormatError

```
public AnnotationFormatError(Throwable cause)
```

Constructs a new `AnnotationFormatError` with the specified cause and a detail message of `(cause == null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Parameters:

`cause - the cause (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.