JavaScript is disabled on your browser.

compact3

java.lang.management

Interface ClassLoadingMXBean

All Superinterfaces:

`PlatformManagedObject`

```
public interface ClassLoadingMXBean
extends PlatformManagedObject
```

The management interface for the class loading system of the Java virtual machine.

A Java virtual machine has a single instance of the implementation class of this interface. This instance implementing this interface is an MXBean that can be obtained by calling the `ManagementFactory.getClassLoadingMXBean()` method or from the `platform MBeanServer`.

The `ObjectName` for uniquely identifying the MXBean for the class loading system within an `MBeanServer` is:

```
java.lang:type=ClassLoading
```

It can be obtained by calling the `PlatformManagedObject.getObjectName()` method.

Since:

1.5

See Also:

`ManagementFactory.getPlatformMXBeans(Class)`, `JMX Specification.`, `Ways to Access MXBeans`

Method Summary

Abstract Methods

Modifier and Type	Method	Description
int	**getLoadedClassCount**()	Returns the number of classes that are currently loaded in the Java virtual machine.
long	**getTotalLoadedClassCount**()	Returns the total number of classes that have been loaded since the Java virtual machine has started execution.
long	**getUnloadedClassCount**()	Returns the total number of classes unloaded since the Java virtual machine has started execution.
boolean	**isVerbose**()	Tests if the verbose output for the class loading system is enabled.
void	**setVerbose**(boolean value)	Enables or disables the verbose output for the class loading system.

Methods inherited from interface java.lang.management.PlatformManagedObject

getObjectName

Method Detail

getTotalLoadedClassCount

```
long getTotalLoadedClassCount()
```

Returns the total number of classes that have been loaded since the Java virtual machine has started execution.

Returns:

the total number of classes loaded.

getLoadedClassCount

```
int getLoadedClassCount()
```

Returns the number of classes that are currently loaded in the Java virtual machine.

Returns:

the number of currently loaded classes.

getUnloadedClassCount

```
long getUnloadedClassCount()
```

Returns the total number of classes unloaded since the Java virtual machine has started execution.

Returns:

the total number of unloaded classes.

isVerbose

```
boolean isVerbose()
```

Tests if the verbose output for the class loading system is enabled.

Returns:

true if the verbose output for the class loading system is enabled; false otherwise.

setVerbose

```
void setVerbose(boolean value)
```

Enables or disables the verbose output for the class loading system. The verbose output information and the output stream to which the verbose information is emitted are implementation dependent. Typically, a Java virtual machine implementation prints a message each time a class file is loaded.

This method can be called by multiple threads concurrently. Each invocation of this method enables or disables the verbose output globally.

Parameters:

`value - true to enable the verbose output; false to disable.`

Throws:

`SecurityException - if a security manager exists and the caller does not have ManagementPermission("control").`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.