JavaScript is disabled on your browser.

compact3

java.lang.management

Interface CompilationMXBean

All Superinterfaces:

`PlatformManagedObject`

```
public interface CompilationMXBean
extends PlatformManagedObject
```

The management interface for the compilation system of the Java virtual machine.

A Java virtual machine has a single instance of the implementation class of this interface. This instance implementing this interface is an MXBean that can be obtained by calling the `ManagementFactory.getCompilationMXBean()` method or from the `platform MBeanServer` method.

The `ObjectName` for uniquely identifying the MXBean for the compilation system within an MBeanServer is:

```
java.lang:type=Compilation
```

It can be obtained by calling the `PlatformManagedObject.getObjectName()` method.

Since:

1.5

See Also:

`ManagementFactory.getPlatformMXBeans(Class)`, `JMX Specification.`, `Ways to Access MXBeans`

Method Summary

Abstract Methods

Modifier and Type	Method	Description
String	getName()	Returns the name of the Just-in-time (JIT) compiler.
long	getTotalCompilationTime()	Returns the approximate accumulated elapsed time (in milliseconds) spent in compilation.
boolean	isCompilationTimeMonitoringSupported()	Tests if the Java virtual machine supports the monitoring of compilation time.

Methods inherited from interface java.lang.management.PlatformManagedObject

getObjectName

Method Detail

getName

String getName()

Returns the name of the Just-in-time (JIT) compiler.

Returns:

the name of the JIT compiler.

isCompilationTimeMonitoringSupported

```
boolean isCompilationTimeMonitoringSupported()
```

Tests if the Java virtual machine supports the monitoring of compilation time.

Returns:

`true if the monitoring of compilation time is supported ; false otherwise.`

getTotalCompilationTime

```
long getTotalCompilationTime()
```

Returns the approximate accumulated elapsed time (in milliseconds) spent in compilation. If multiple threads are used for compilation, this value is summation of the approximate time that each thread spent in compilation.

This method is optionally supported by the platform. A Java virtual machine implementation may not support the compilation time monitoring. The `isCompilationTimeMonitoringSupported()` method can be used to determine if the Java virtual machine supports this operation.

This value does not indicate the level of performance of the Java virtual machine and is not intended for performance comparisons of different virtual machine implementations. The implementations may have different definitions and different measurements of the compilation time.

Returns:

`Compilation time in milliseconds`

Throws:

`UnsupportedOperationException - if the Java virtual machine does not support this operation.`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.