JavaScript is disabled on your browser.

compact3

java.lang.management

Interface GarbageCollectorMXBean

All Superinterfaces:

`MemoryManagerMXBean, PlatformManagedObject`

```
public interface GarbageCollectorMXBean
extends MemoryManagerMXBean
```

The management interface for the garbage collection of the Java virtual machine. Garbage collection is the process that the Java virtual machine uses to find and reclaim unreachable objects to free up memory space. A garbage collector is one type of `memory manager`.

A Java virtual machine may have one or more instances of the implementation class of this interface. An instance implementing this interface is an MXBean that can be obtained by calling the `ManagementFactory.getGarbageCollectorMXBeans()` method or from the `platform MBeanServer` method.

The `ObjectName` for uniquely identifying the MXBean for a garbage collector within an MBeanServer is:

> `java.lang:type=GarbageCollector,name=`*collector's name*

It can be obtained by calling the `PlatformManagedObject.getObjectName()` method. A platform usually includes additional platform-dependent information specific to a garbage collection algorithm for monitoring.

Since:

1.5

See Also:

ManagementFactory.getPlatformMXBeans(Class), MemoryMXBean, JMX Specification., Ways to Access MXBeans

Method Summary

Abstract Methods

Modifier and Type	Method	Description
long	getCollectionCount()	Returns the total number of collections that have occurred.
long	getCollectionTime()	Returns the approximate accumulated collection elapsed time in milliseconds.

Methods inherited from interface java.lang.management.MemoryManagerMXBean

getMemoryPoolNames, getName, isValid

Methods inherited from interface java.lang.management.PlatformManagedObject

getObjectName

Method Detail

getCollectionCount

```
long getCollectionCount()
```

Returns the total number of collections that have occurred. This method returns -1 if the collection count is undefined for this collector.

Returns:

the total number of collections that have occurred.

getCollectionTime

```
long getCollectionTime()
```

Returns the approximate accumulated collection elapsed time in milliseconds. This method returns `-1` if the collection elapsed time is undefined for this collector.

The Java virtual machine implementation may use a high resolution timer to measure the elapsed time. This method may return the same value even if the collection count has been incremented if the collection elapsed time is very short.

Returns:

`the approximate accumulated collection elapsed time in milliseconds.`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.