JavaScript is disabled on your browser.

compact3

java.lang.management

Class LockInfo

java.lang.Object
    java.lang.management.LockInfo

Direct Known Subclasses:

MonitorInfo

```
public class LockInfo
extends Object
```

Information about a *lock*. A lock can be a built-in object monitor, an *ownable synchronizer*, or the Condition object associated with synchronizers.

An ownable synchronizer is a synchronizer that may be exclusively owned by a thread and uses AbstractOwnableSynchronizer (or its subclass) to implement its synchronization property. ReentrantLock and ReentrantReadWriteLock are two examples of ownable synchronizers provided by the platform.

MXBean Mapping

LockInfo is mapped to a CompositeData as specified in the from method.

Since:

1.6

See Also:

AbstractOwnableSynchronizer, Condition

Constructor Summary

Constructors

Constructor	Description

LockInfo(**String** className, int identityHashCode)	Constructs a LockInfo object.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
static **LockInfo**	**from**(**CompositeData** cd)	Returns a LockInfo object represented by the given CompositeData.
String	**getClassName**()	Returns the fully qualified name of the class of the lock object.
int	**getIdentityHashCode**()	Returns the identity hash code of the lock object returned from the **System.identityHashCode(java.lang.Object** method.
String	**toString**()	Returns a string representation of a lock.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

LockInfo

```
public LockInfo(String className,
                int identityHashCode)
```

Constructs a LockInfo object.

Parameters:

className - the fully qualified name of the class of the lock object.

identityHashCode - the identity hash code of the lock object.

Method Detail

getClassName

```
public String getClassName()
```

Returns the fully qualified name of the class of the lock object.

Returns:

the fully qualified name of the class of the lock object.

getIdentityHashCode

```
public int getIdentityHashCode()
```

Returns the identity hash code of the lock object returned from the `System.identityHashCode(java.lang.Object)` method.

Returns:

the identity hash code of the lock object.

from

```
public static LockInfo from(CompositeData cd)
```

Returns a `LockInfo` object represented by the given `CompositeData`. The given `CompositeData` must contain the following attributes:

Attribute Name	Type
className	`java.lang.String`
identityHashCode	`java.lang.Integer`

Parameters:

cd - CompositeData representing a LockInfo

Returns:

a LockInfo object represented by cd if cd is not null; null otherwise.

Throws:

`IllegalArgumentException` - if cd does not represent a LockInfo with the attributes described above.

Since:

1.8

toString

```
public String toString()
```

Returns a string representation of a lock. The returned string representation consists of the name of the class of the lock object, the at-sign character `@', and the unsigned hexadecimal representation of the *identity* hash code of the object. This method returns a string equals to the value of:

```
lock.getClass().getName() + '@' + Integer.toHexString(System.identityHashCo
```

where `lock` is the lock object.

Overrides:

`toString` in class `Object`

Returns:

the string representation of a lock.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.