JavaScript is disabled on your browser.

compact3

java.lang.management

Class ManagementPermission

java.lang.Object
  java.security.Permission
    java.security.BasicPermission
      java.lang.management.ManagementPermission

All Implemented Interfaces:

Serializable, Guard

```
public final class ManagementPermission
extends BasicPermission
```

The permission which the SecurityManager will check when code that is running with a SecurityManager calls methods defined in the management interface for the Java platform.

The following table provides a summary description of what the permission allows, and discusses the risks of granting code the permission.

Permission Target Name	What the Permission Allows	Risks of Allowing this Permission
control	Ability to control the runtime characteristics of the Java virtual machine, for example, enabling and disabling the verbose output for the class loading or memory system, setting the threshold of a memory pool, and enabling and disabling the thread contention monitoring support. Some actions controlled by this permission can disclose information about the	This allows an attacker to control the runtime characteristics of the Java virtual machine and cause the system to misbehave. An attacker can also access some information related to the running application.

	running application, like the -verbose:class flag.	
monitor	Ability to retrieve runtime information about the Java virtual machine such as thread stack trace, a list of all loaded class names, and input arguments to the Java virtual machine.	This allows malicious code to monitor runtime information and uncover vulnerabilities.

Programmers do not normally create ManagementPermission objects directly. Instead they are created by the security policy code based on reading the security policy file.

Since:

1.5

See Also:

BasicPermission, Permission, Permissions, PermissionCollection, SecurityManager, Serialized Form

Constructor Summary

Constructors

Constructor	Description
`ManagementPermission(String name)`	Constructs a ManagementPermission with the specified name.
`ManagementPermission(String name, String actions)`	Constructs a new ManagementPermission object.

Method Summary

Methods inherited from class java.security.BasicPermission

equals, getActions, hashCode, implies, newPermissionCollection

Methods inherited from class java.security.Permission

checkGuard, getName, toString

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Constructor Detail

ManagementPermission

```
public ManagementPermission(String name)
```

Constructs a ManagementPermission with the specified name.

Parameters:

name - Permission name. Must be either "monitor" or "control".

Throws:

NullPointerException - if name is null.

IllegalArgumentException - if name is empty or invalid.

ManagementPermission

```
public ManagementPermission(String name,
                            String actions)
                     throws IllegalArgumentException
```

Constructs a new ManagementPermission object.

Parameters:

name - Permission name. Must be either "monitor" or "control".

actions - Must be either null or the empty string.

Throws:

NullPointerException - if name is null.

`IllegalArgumentException` - if name is empty or if arguments are invalid.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.