JavaScript is disabled on your browser.

compact3

java.lang.management

Class MonitorInfo

java.lang.Object
    java.lang.management.LockInfo
        java.lang.management.MonitorInfo

```
public class MonitorInfo
extends LockInfo
```

Information about an object monitor lock. An object monitor is locked when entering a synchronization block or method on that object.

MXBean Mapping

`MonitorInfo` is mapped to a `CompositeData` with attributes as specified in the `from` method.

Since:

1.6

Constructor Summary

Constructors

Constructor
`MonitorInfo(String className, int identityHashCode, int stackDepth, StackTraceEle`

Method Summary

Instance Methods

Concrete Methods

Modifier and Type	Method	Description
static MonitorInfo	from(CompositeData cd)	Returns a MonitorInfo object represented by the given CompositeData.
int	getLockedStackDepth()	Returns the depth in the stack trace where the object monitor was locked.
StackTraceElement	getLockedStackFrame()	Returns the stack frame that locked the object monitor.

Methods inherited from class java.lang.management.LockInfo

getClassName, getIdentityHashCode, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

MonitorInfo

```
public MonitorInfo(String className,
                   int identityHashCode,
                   int stackDepth,
                   StackTraceElement stackFrame)
```

Construct a MonitorInfo object.

Parameters:

className - the fully qualified name of the class of the lock object.

identityHashCode - the identity hash code of the lock object.

stackDepth - the depth in the stack trace where the object monitor was locked.

stackFrame - the stack frame that locked the object monitor.

Throws:

IllegalArgumentException - if stackDepth ≥ 0 but stackFrame is null, or stackDepth < 0 but stackFrame is not null.

Method Detail

getLockedStackDepth

public int getLockedStackDepth()

Returns the depth in the stack trace where the object monitor was locked. The depth is the index to the StackTraceElement array returned in the ThreadInfo.getStackTrace() method.

Returns:

the depth in the stack trace where the object monitor was locked, or a negative number if not available.

getLockedStackFrame

public StackTraceElement getLockedStackFrame()

Returns the stack frame that locked the object monitor.

Returns:

StackTraceElement that locked the object monitor, or null if not available.

from

public static MonitorInfo from(CompositeData cd)

Returns a MonitorInfo object represented by the given CompositeData. The given CompositeData must contain the following attributes as well as the attributes specified in the mapped type for the LockInfo class:

Attribute Name	Type
lockedStackFrame	CompositeData as specified in the stackTrace attribute defined in the ThreadInfo.from method.

lockedStackDepth java.lang.Integer

Parameters:

cd - CompositeData representing a MonitorInfo

Returns:

a MonitorInfo object represented by cd if cd is not null; null otherwise.

Throws:

IllegalArgumentException - if cd does not represent a MonitorInfo with the attributes described above.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.