JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang.ref

Class PhantomReference<T>

java.lang.Object
    java.lang.ref.Reference<T>
        java.lang.ref.PhantomReference<T>

```
public class PhantomReference<T>
extends Reference<T>
```

Phantom reference objects, which are enqueued after the collector determines that their referents may otherwise be reclaimed. Phantom references are most often used to schedule post-mortem cleanup actions.

Suppose the garbage collector determines at a certain point in time that an object is phantom reachable. At that time it will atomically clear all phantom references to that object and all phantom references to any other phantom-reachable objects from which that object is reachable. At the same time or at some later time it will enqueue those newly-cleared phantom references that are registered with reference queues.

In order to ensure that a reclaimable object remains so, the referent of a phantom reference may not be retrieved: The `get` method of a phantom reference always returns `null`.

Since:

1.2

Constructor Summary

Constructors

Constructor	Description

`PhantomReference(T referent, ReferenceQueue<? super T> q)`	Creates a new phantom reference that refers to the given object and is registered with the given queue.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`T`	`get()`	Returns this reference object's referent.

Methods inherited from class java.lang.ref.Reference

`clear`, `clone`, `enqueue`, `isEnqueued`

Methods inherited from class java.lang.Object

`equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

PhantomReference

```
public PhantomReference(T referent,
                        ReferenceQueue<? super T> q)
```

Creates a new phantom reference that refers to the given object and is registered with the given queue.

It is possible to create a phantom reference with a `null` queue, but such a reference is completely useless: Its `get` method will always return `null` and, since it does not have a queue, it will never be enqueued.

Parameters:

`referent - the object the new phantom reference will refer to`

`q - the queue with which the reference is to be registered, or null if registration is not required`

Method Detail

get

`public T get()`

Returns this reference object's referent. Because the referent of a phantom reference is always inaccessible, this method always returns `null`.

Overrides:

`get in class Reference<T>`

Returns:

`null`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.