JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang.ref

Class ReferenceQueue<T>

java.lang.Object
    java.lang.ref.ReferenceQueue<T>

```
public class ReferenceQueue<T>
extends Object
```

Reference queues, to which registered reference objects are appended by the garbage collector after the appropriate reachability changes are detected.

Since:

1.2

Constructor Summary

Constructors

Constructor	Description
`ReferenceQueue()`	Constructs a new reference-object queue.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`Reference<? extends T>`	`poll()`	Polls this queue to see if a reference object is available.

`Reference<? extends T>`	`remove()`	Removes the next reference object in this queue, blocking until one becomes available.
`Reference<? extends T>`	`remove(long timeout)`	Removes the next reference object in this queue, blocking until either one becomes available or the given timeout period expires.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

ReferenceQueue

```
public ReferenceQueue()
```

Constructs a new reference-object queue.

Method Detail

poll

```
public Reference<? extends T> poll()
```

Polls this queue to see if a reference object is available. If one is available without further delay then it is removed from the queue and returned. Otherwise this method immediately returns `null`.

Returns:

`A reference object, if one was immediately available, otherwise null`

remove

```
public Reference<? extends T> remove(long timeout)
                              throws IllegalArgumentException,
                                     InterruptedException
```

Removes the next reference object in this queue, blocking until either one becomes available or the given timeout period expires.

This method does not offer real-time guarantees: It schedules the timeout as if by invoking the `Object.wait(long)` method.

Parameters:

`timeout - If positive, block for up to timeout milliseconds while waiting for a reference to be added to this queue. If zero, block indefinitely.`

Returns:

`A reference object, if one was available within the specified timeout period, otherwise null`

Throws:

`IllegalArgumentException - If the value of the timeout argument is negative`

`InterruptedException - If the timeout wait is interrupted`

remove

```
public Reference<? extends T> remove()
                              throws InterruptedException
```

Removes the next reference object in this queue, blocking until one becomes available.

Returns:

`A reference object, blocking until one becomes available`

Throws:

```
InterruptedException - If the wait is interrupted
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.