JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang.ref

Class WeakReference<T>

java.lang.Object
    java.lang.ref.Reference<T>
        java.lang.ref.WeakReference<T>

```
public class WeakReference<T>
extends Reference<T>
```

Weak reference objects, which do not prevent their referents from being made finalizable, finalized, and then reclaimed. Weak references are most often used to implement canonicalizing mappings.

Suppose that the garbage collector determines at a certain point in time that an object is weakly reachable. At that time it will atomically clear all weak references to that object and all weak references to any other weakly-reachable objects from which that object is reachable through a chain of strong and soft references. At the same time it will declare all of the formerly weakly-reachable objects to be finalizable. At the same time or at some later time it will enqueue those newly-cleared weak references that are registered with reference queues.

Since:

1.2

Constructor Summary

Constructors

Constructor	Description
`WeakReference(T referent)`	Creates a new weak reference

	that refers to the given object.
`WeakReference(T referent, ReferenceQueue<? super T> q)`	Creates a new weak reference that refers to the given object and is registered with the given queue.

Method Summary

Methods inherited from class java.lang.ref.Reference

`clear`, `clone`, `enqueue`, `get`, `isEnqueued`

Methods inherited from class java.lang.Object

`equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

WeakReference

```
public WeakReference(T referent)
```

Creates a new weak reference that refers to the given object. The new reference is not registered with any queue.

Parameters:

`referent` - object the new weak reference will refer to

WeakReference

```
public WeakReference(T referent,
                     ReferenceQueue<? super T> q)
```

Creates a new weak reference that refers to the given object and is registered with the given queue.

Parameters:

`referent - object the new weak reference will refer to`

`q - the queue with which the reference is to be registered, or null if registration is not required`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.