JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang.reflect

Class Array

java.lang.Object
    java.lang.reflect.Array

```
public final class Array
extends Object
```

The `Array` class provides static methods to dynamically create and access Java arrays.

`Array` permits widening conversions to occur during a get or set operation, but throws an `IllegalArgumentException` if a narrowing conversion would occur.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
static **Object**	**get**(**Object** array, int index)	Returns the value of the indexed component in the specified array object.
static boolean	**getBoolean**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as a `boolean`.
static byte	**getByte**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as a `byte`.

static char	**getChar**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as a char.
static double	**getDouble**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as a double.
static float	**getFloat**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as a float.
static int	**getInt**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as an int.
static int	**getLength**(**Object** array)	Returns the length of the specified array object, as an int.
static long	**getLong**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as a long.
static short	**getShort**(**Object** array, int index)	Returns the value of the indexed component in the specified array object, as a short.
static **Object**	**newInstance**(**Class**<? > componentType, int... dimensions)	Creates a new array with the specified component type and dimensions.
static **Object**	**newInstance**(**Class**<? > componentType, int length)	Creates a new array with the specified component type and length.
static void	**set**(**Object** array, int index, **Object** value)	Sets the value of the indexed component of the specified array object to the specified new value.
static void	**setBoolean**(**Object** array, int index, boolean z)	Sets the value of the indexed component of the

		specified array object to the specified `boolean` value.
static void	**setByte**(**Object** array, int index, byte b)	Sets the value of the indexed component of the specified array object to the specified `byte` value.
static void	**setChar**(**Object** array, int index, char c)	Sets the value of the indexed component of the specified array object to the specified `char` value.
static void	**setDouble**(**Object** array, int index, double d)	Sets the value of the indexed component of the specified array object to the specified `double` value.
static void	**setFloat**(**Object** array, int index, float f)	Sets the value of the indexed component of the specified array object to the specified `float` value.
static void	**setInt**(**Object** array, int index, int i)	Sets the value of the indexed component of the specified array object to the specified `int` value.
static void	**setLong**(**Object** array, int index, long l)	Sets the value of the indexed component of the specified array object to the specified `long` value.
static void	**setShort**(**Object** array, int index, short s)	Sets the value of the indexed component of the specified array object to the specified `short` value.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Method Detail

newInstance

```
public static Object newInstance(Class<?> componentType,
                                 int length)
                          throws NegativeArraySizeException
```

Creates a new array with the specified component type and length. Invoking this method is equivalent to creating an array as follows:

```
int[] x = {length};
Array.newInstance(componentType, x);
```

The number of dimensions of the new array must not exceed 255.

Parameters:

`componentType` - the Class object representing the component type of the new array

`length` - the length of the new array

Returns:

the new array

Throws:

`NullPointerException` - if the specified componentType parameter is null

`IllegalArgumentException` - if componentType is `Void.TYPE` or if the number of dimensions of the requested array instance exceed 255.

`NegativeArraySizeException` - if the specified length is negative

newInstance

```
public static Object newInstance(Class<?> componentType,
                                 int... dimensions)
                          throws IllegalArgumentException,
                                 NegativeArraySizeException
```

Creates a new array with the specified component type and dimensions. If `componentType` represents a non-array class or interface, the new array has `dimensions.length` dimensions and `componentType` as its component type. If `componentType` represents an array class, the number of dimensions of the new array is equal to the sum of `dimensions.length` and the number of dimensions of `componentType`. In this case, the component type of the new array is the component type of `componentType`.

The number of dimensions of the new array must not exceed 255.

Parameters:

componentType - the Class object representing the component type of the new array

dimensions - an array of int representing the dimensions of the new array

Returns:

the new array

Throws:

NullPointerException - if the specified componentType argument is null

IllegalArgumentException - if the specified dimensions argument is a zero-dimensional array, if componentType is Void.TYPE, or if the number of dimensions of the requested array instance exceed 255.

NegativeArraySizeException - if any of the components in the specified dimensions argument is negative.

getLength

```
public static int getLength(Object array)
                     throws IllegalArgumentException
```

Returns the length of the specified array object, as an int.

Parameters:

array - the array

Returns:

the length of the array

Throws:

IllegalArgumentException - if the object argument is not an array

get

```
public static Object get(Object array,
                         int index)
                  throws IllegalArgumentException,
                         ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object. The value is automatically wrapped in an object if it has a primitive type.

Parameters:

array - the array

index - the index

Returns:

the (possibly wrapped) value of the indexed component in the specified array

Throws:

NullPointerException - If the specified object is null

IllegalArgumentException - If the specified object is not an array

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

getBoolean

```
public static boolean getBoolean(Object array,
                                 int index)
                          throws IllegalArgumentException,
                                 ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as a boolean.

Parameters:

array - the array

index - the index

Returns:

the value of the indexed component in the specified array

Throws:

NullPointerException - If the specified object is null

IllegalArgumentException - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

get(java.lang.Object, int)

getByte

```
public static byte getByte(Object array,
                           int index)
```

```
                    throws IllegalArgumentException,
                           ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as a byte.

Parameters:

array - the array

index - the index

Returns:

the value of the indexed component in the specified array

Throws:

NullPointerException - If the specified object is null

IllegalArgumentException - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

get(java.lang.Object, int)

getChar

```
public static char getChar(Object array,
                           int index)
                    throws IllegalArgumentException,
                           ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as a char.

Parameters:

array - the array

index - the index

Returns:

the value of the indexed component in the specified array

Throws:

NullPointerException - If the specified object is null

IllegalArgumentException - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

get(java.lang.Object, int)

getShort

```
public static short getShort(Object array,
                             int index)
                      throws IllegalArgumentException,
                             ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as a short.

Parameters:

array - the array

index - the index

Returns:

the value of the indexed component in the specified array

Throws:

NullPointerException - If the specified object is null

IllegalArgumentException - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

get(java.lang.Object, int)

getInt

```
public static int getInt(Object array,
                         int index)
                  throws IllegalArgumentException,
                         ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as an int.

Parameters:

array - the array

index - the index

Returns:

the value of the indexed component in the specified array

Throws:

NullPointerException - If the specified object is null

IllegalArgumentException - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

get(java.lang.Object, int)

getLong

```
public static long getLong(Object array,
                           int index)
                    throws IllegalArgumentException,
                           ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as a long.

Parameters:

array - the array

index - the index

Returns:

the value of the indexed component in the specified array

Throws:

NullPointerException - If the specified object is null

IllegalArgumentException - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

get(java.lang.Object, int)

getFloat

```
public static float getFloat(Object array,
                             int index)
                      throws IllegalArgumentException,
                             ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as a `float`.

Parameters:

`array` - the array

`index` - the index

Returns:

the value of the indexed component in the specified array

Throws:

`NullPointerException` - If the specified object is null

`IllegalArgumentException` - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

`ArrayIndexOutOfBoundsException` - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

`get(java.lang.Object, int)`

getDouble

```
public static double getDouble(Object array,
                               int index)
                        throws IllegalArgumentException,
                               ArrayIndexOutOfBoundsException
```

Returns the value of the indexed component in the specified array object, as a `double`.

Parameters:

`array` - the array

`index` - the index

Returns:

the value of the indexed component in the specified array

Throws:

`NullPointerException` - If the specified object is null

IllegalArgumentException - If the specified object is not an array, or if the indexed element cannot be converted to the return type by an identity or widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

get(java.lang.Object, int)

set

```
public static void set(Object array,
                       int index,
                       Object value)
                throws IllegalArgumentException,
                       ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified new value. The new value is first automatically unwrapped if the array has a primitive component type.

Parameters:

array - the array

index - the index into the array

value - the new value of the indexed component

Throws:

NullPointerException - If the specified object argument is null

IllegalArgumentException - If the specified object argument is not an array, or if the array component type is primitive and an unwrapping conversion fails

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

setBoolean

```
public static void setBoolean(Object array,
                              int index,
                              boolean z)
                       throws IllegalArgumentException,
                              ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified `boolean` value.

Parameters:

`array` - the array

`index` - the index into the array

`z` - the new value of the indexed component

Throws:

`NullPointerException` - If the specified object argument is null

`IllegalArgumentException` - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

`ArrayIndexOutOfBoundsException` - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

`set(java.lang.Object, int, java.lang.Object)`

setByte

```
public static void setByte(Object array,
                           int index,
                           byte b)
                    throws IllegalArgumentException,
                           ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified `byte` value.

Parameters:

`array` - the array

`index` - the index into the array

`b` - the new value of the indexed component

Throws:

`NullPointerException` - If the specified object argument is null

`IllegalArgumentException` - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

`ArrayIndexOutOfBoundsException` - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

set(java.lang.Object, int, java.lang.Object)

setChar

```
public static void setChar(Object array,
                           int index,
                           char c)
                    throws IllegalArgumentException,
                           ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified `char` value.

Parameters:

`array` - the array

`index` - the index into the array

`c` - the new value of the indexed component

Throws:

`NullPointerException` - If the specified object argument is null

`IllegalArgumentException` - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

`ArrayIndexOutOfBoundsException` - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

set(java.lang.Object, int, java.lang.Object)

setShort

```
public static void setShort(Object array,
                            int index,
                            short s)
                     throws IllegalArgumentException,
                            ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified `short` value.

Parameters:

`array` - the array

`index` - the index into the array

s - the new value of the indexed component

Throws:

NullPointerException - If the specified object argument is null

IllegalArgumentException - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

set(java.lang.Object, int, java.lang.Object)

setInt

```
public static void setInt(Object array,
                          int index,
                          int i)
                   throws IllegalArgumentException,
                          ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified int value.

Parameters:

array - the array

index - the index into the array

i - the new value of the indexed component

Throws:

NullPointerException - If the specified object argument is null

IllegalArgumentException - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

set(java.lang.Object, int, java.lang.Object)

setLong

```
public static void setLong(Object array,
                           int index,
                           long l)
                    throws IllegalArgumentException,
                           ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified `long` value.

Parameters:

`array` - the array

`index` - the index into the array

`l` - the new value of the indexed component

Throws:

`NullPointerException` - If the specified object argument is null

`IllegalArgumentException` - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

`ArrayIndexOutOfBoundsException` - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

`set(java.lang.Object, int, java.lang.Object)`

setFloat

```
public static void setFloat(Object array,
                            int index,
                            float f)
                     throws IllegalArgumentException,
                            ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified `float` value.

Parameters:

`array` - the array

`index` - the index into the array

`f` - the new value of the indexed component

Throws:

NullPointerException - If the specified object argument is null

IllegalArgumentException - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

set(java.lang.Object, int, java.lang.Object)

setDouble

```
public static void setDouble(Object array,
                             int index,
                             double d)
                      throws IllegalArgumentException,
                             ArrayIndexOutOfBoundsException
```

Sets the value of the indexed component of the specified array object to the specified double value.

Parameters:

array - the array

index - the index into the array

d - the new value of the indexed component

Throws:

NullPointerException - If the specified object argument is null

IllegalArgumentException - If the specified object argument is not an array, or if the specified value cannot be converted to the underlying array's component type by an identity or a primitive widening conversion

ArrayIndexOutOfBoundsException - If the specified index argument is negative, or if it is greater than or equal to the length of the specified array

See Also:

C

```
set(java.lang.Object, int, java.lang.Object)
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.