JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang.reflect

Interface ParameterizedType

All Superinterfaces:

Type

```
public interface ParameterizedType
extends Type
```

ParameterizedType represents a parameterized type such as Collection<String>.

A parameterized type is created the first time it is needed by a reflective method, as specified in this package. When a parameterized type p is created, the generic type declaration that p instantiates is resolved, and all type arguments of p are created recursively. See TypeVariable for details on the creation process for type variables. Repeated creation of a parameterized type has no effect.

Instances of classes that implement this interface must implement an equals() method that equates any two instances that share the same generic type declaration and have equal type parameters.

Since:

1.5

Method Summary

Abstract Methods

Modifier and Type	Method	Description
Type[]	getActualTypeArguments()	Returns an array of Type objects representing the

		actual type arguments to this type.
Type	getOwnerType()	Returns a Type object representing the type that this type is a member of.
Type	getRawType()	Returns the Type object representing the class or interface that declared this type.

Methods inherited from interface java.lang.reflect.Type

getTypeName

Method Detail

getActualTypeArguments

```
Type[] getActualTypeArguments()
```

Returns an array of Type objects representing the actual type arguments to this type.

Note that in some cases, the returned array be empty. This can occur if this type represents a non-parameterized type nested within a parameterized type.

Returns:

an array of Type objects representing the actual type arguments to this type

Throws:

TypeNotPresentException - if any of the actual type arguments refers to a non-existent type declaration

MalformedParameterizedTypeException - if any of the actual type parameters refer to a parameterized type that cannot be instantiated for any reason

Since:

1.5

getRawType

`Type getRawType()`

Returns the `Type` object representing the class or interface that declared this type.

Returns:

`the Type object representing the class or interface that declared this type`

Since:

`1.5`

getOwnerType

`Type getOwnerType()`

Returns a `Type` object representing the type that this type is a member of. For example, if this type is `O<T>.I<S>`, return a representation of `O<T>`.

If this type is a top-level type, `null` is returned.

Returns:

`a Type object representing the type that this type is a member of. If this type is a top-level type, null is returned`

Throws:

`TypeNotPresentException - if the owner type refers to a non-existent type declaration`

`MalformedParameterizedTypeException - if the owner type refers to a parameterized type that cannot be instantiated for any reason`

Since:

```
1.5
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.