JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio

Class InvalidMarkException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalStateException
          java.nio.InvalidMarkException

All Implemented Interfaces:

Serializable

```
public class InvalidMarkException
extends IllegalStateException
```

Unchecked exception thrown when an attempt is made to reset a buffer when its mark is not defined.

Since:

1.4

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`InvalidMarkException()`	Constructs an instance of this class.

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

InvalidMarkException

```
public InvalidMarkException()
```

Constructs an instance of this class.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.