JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.channels

Class Channels

java.lang.Object
    java.nio.channels.Channels

```
public final class Channels
extends Object
```

Utility methods for channels and streams.

This class defines static methods that support the interoperation of the stream classes of the `java.io` package with the channel classes of this package.

Since:

1.4

Method Summary

Concrete Methods

Modifier and Type	Method	Descriptio
static ReadableByteChannel	newChannel(InputStream in)	Construct a channel that reads bytes fron the given stream.
static WritableByteChannel	newChannel(OutputStream out)	Construct a channel that write bytes to

		the given stream.
static **InputStream**	**newInputStream**(**AsynchronousByteChannel** ch)	Construct a stream that reads bytes from the given channel.
static **InputStream**	**newInputStream**(**ReadableByteChannel** ch)	Construct a stream that reads bytes from the given channel.
static **OutputStream**	**newOutputStream**(**AsynchronousByteChannel** ch)	Construct a stream that write bytes to the given channel.
static **OutputStream**	**newOutputStream**(**WritableByteChannel** ch)	Construct a stream that write bytes to the given channel.
static **Reader**	**newReader**(**ReadableByteChannel** ch, **CharsetDecoder** dec, int minBufferCap)	Construct a reader that decodes bytes from the given channel using the given decoder.
static **Reader**	**newReader**(**ReadableByteChannel** ch, **String** csName)	Construct a reader that decodes bytes from the given channel according

		to the named charset.
static **Writer**	**newWriter**(**WritableByteChannel** ch, **CharsetEncoder** enc, int minBufferCap)	Construct a writer that encodes character using the given encoder and write the resulting bytes to the given channel.
static **Writer**	**newWriter**(**WritableByteChannel** ch, **String** csName)	Construct a writer that encodes character according to the named charset and write the resulting bytes to the given channel.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

newInputStream

public static InputStream newInputStream(ReadableByteChannel ch)

Constructs a stream that reads bytes from the given channel.

The `read` methods of the resulting stream will throw an `IllegalBlockingModeException` if invoked while the underlying channel is in non-blocking mode. The stream will not be buffered, and it will not support the `mark` or `reset` methods. The stream will be safe for access by multiple concurrent threads. Closing the stream will in turn cause the channel to be closed.

Parameters:

`ch - The channel from which bytes will be read`

Returns:

`A new input stream`

newOutputStream

```
public static OutputStream newOutputStream(WritableByteChannel ch)
```

Constructs a stream that writes bytes to the given channel.

The `write` methods of the resulting stream will throw an `IllegalBlockingModeException` if invoked while the underlying channel is in non-blocking mode. The stream will not be buffered. The stream will be safe for access by multiple concurrent threads. Closing the stream will in turn cause the channel to be closed.

Parameters:

`ch - The channel to which bytes will be written`

Returns:

`A new output stream`

newInputStream

```
public static InputStream newInputStream(AsynchronousByteChannel ch)
```

Constructs a stream that reads bytes from the given channel.

The stream will not be buffered, and it will not support the `mark` or `reset` methods. The stream will be safe for access by multiple concurrent threads. Closing the stream will in turn cause the channel to be closed.

Parameters:

`ch - The channel from which bytes will be read`

Returns:

`A new input stream`

Since:

`1.7`

newOutputStream

```
public static OutputStream newOutputStream(AsynchronousByteChannel ch)
```

Constructs a stream that writes bytes to the given channel.

The stream will not be buffered. The stream will be safe for access by multiple concurrent threads. Closing the stream will in turn cause the channel to be closed.

Parameters:

`ch - The channel to which bytes will be written`

Returns:

`A new output stream`

Since:

`1.7`

newChannel

```
public static ReadableByteChannel newChannel(InputStream in)
```

Constructs a channel that reads bytes from the given stream.

The resulting channel will not be buffered; it will simply redirect its I/O operations to the given stream. Closing the channel will in turn cause the stream to be closed.

Parameters:

in - The stream from which bytes are to be read

Returns:

A new readable byte channel

newChannel

```
public static WritableByteChannel newChannel(OutputStream out)
```

Constructs a channel that writes bytes to the given stream.

The resulting channel will not be buffered; it will simply redirect its I/O operations to the given stream. Closing the channel will in turn cause the stream to be closed.

Parameters:

out - The stream to which bytes are to be written

Returns:

A new writable byte channel

newReader

```
public static Reader newReader(ReadableByteChannel ch,
                               CharsetDecoder dec,
                               int minBufferCap)
```

Constructs a reader that decodes bytes from the given channel using the given decoder.

The resulting stream will contain an internal input buffer of at least `minBufferCap` bytes. The stream's `read` methods will, as needed, fill the buffer by reading bytes from the underlying channel; if the channel is in non-blocking mode when bytes are to be read then an `IllegalBlockingModeException` will be thrown. The resulting stream will not otherwise be buffered, and it will not support the `mark` or `reset` methods. Closing the stream will in turn cause the channel to be closed.

Parameters:

ch - The channel from which bytes will be read

dec - The charset decoder to be used

minBufferCap - The minimum capacity of the internal byte buffer, or -1 if an implementation-dependent default capacity is to be used

Returns:

A new reader

newReader

```
public static Reader newReader(ReadableByteChannel ch,
                               String csName)
```

Constructs a reader that decodes bytes from the given channel according to the named charset.

An invocation of this method of the form

```
Channels.newReader(ch, csname)
```

behaves in exactly the same way as the expression

```
Channels.newReader(ch,
                   Charset.forName(csName)
                       .newDecoder(),
                   -1);
```

Parameters:

`ch` - The channel from which bytes will be read

`csName` - The name of the charset to be used

Returns:

A new reader

Throws:

`UnsupportedCharsetException` - If no support for the named charset is available in this instance of the Java virtual machine

newWriter

```
public static Writer newWriter(WritableByteChannel ch,
                               CharsetEncoder enc,
                               int minBufferCap)
```

Constructs a writer that encodes characters using the given encoder and writes the resulting bytes to the given channel.

The resulting stream will contain an internal output buffer of at least `minBufferCap` bytes. The stream's `write` methods will, as needed, flush the buffer by writing bytes to the underlying channel; if the channel is in non-blocking mode when bytes are to be written then an `IllegalBlockingModeException` will be thrown. The resulting stream will not otherwise be buffered. Closing the stream will in turn cause the channel to be closed.

Parameters:

`ch` - The channel to which bytes will be written

enc - The charset encoder to be used

minBufferCap - The minimum capacity of the internal byte buffer, or -1 if an implementation-dependent default capacity is to be used

Returns:

A new writer

newWriter

```
public static Writer newWriter(WritableByteChannel ch,
                               String csName)
```

Constructs a writer that encodes characters according to the named charset and writes the resulting bytes to the given channel.

An invocation of this method of the form

```
Channels.newWriter(ch, csname)
```

behaves in exactly the same way as the expression

```
Channels.newWriter(ch,
                   Charset.forName(csName)
                       .newEncoder(),
                   -1);
```

Parameters:

ch - The channel to which bytes will be written

csName - The name of the charset to be used

Returns:

A new writer

Throws:

`UnsupportedCharsetException` - If no support for the named charset is available in this instance of the Java virtual machine

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.