JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.channels

Interface CompletionHandler<V,A>

Type Parameters:

`V - The result type of the I/O operation`

`A - The type of the object attached to the I/O operation`

`public interface` **`CompletionHandler<V,A>`**

A handler for consuming the result of an asynchronous I/O operation.

The asynchronous channels defined in this package allow a completion handler to be specified to consume the result of an asynchronous operation. The `completed` method is invoked when the I/O operation completes successfully. The `failed` method is invoked if the I/O operations fails. The implementations of these methods should complete in a timely manner so as to avoid keeping the invoking thread from dispatching to other completion handlers.

Since:

`1.7`

Method Summary

Abstract Methods

Modifier and Type	Method	Description
`void`	`completed(V result, A attachment)`	Invoked when an operation has completed.

void	**failed**(**Throwable** exc, **A** attachment)	Invoked when an operation fails.

Method Detail

completed

```
void completed(V result,
               A attachment)
```

Invoked when an operation has completed.

Parameters:

`result - The result of the I/O operation.`

`attachment - The object attached to the I/O operation when it was initiated.`

failed

```
void failed(Throwable exc,
            A attachment)
```

Invoked when an operation fails.

Parameters:

`exc - The exception to indicate why the I/O operation failed`

`attachment - The object attached to the I/O operation when it was initiated.`

contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.