JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.channels

Class IllegalBlockingModeException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalStateException
          java.nio.channels.IllegalBlockingModeException

All Implemented Interfaces:

Serializable

```
public class IllegalBlockingModeException
extends IllegalStateException
```

Unchecked exception thrown when a blocking-mode-specific operation is invoked upon a channel in the incorrect blocking mode.

Since:

1.4

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IllegalBlockingModeException()`	Constructs an instance of this class.

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

IllegalBlockingModeException

```
public IllegalBlockingModeException()
```

Constructs an instance of this class.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.