JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.channels

Class MembershipKey

java.lang.Object
    java.nio.channels.MembershipKey

```
public abstract class MembershipKey
extends Object
```

A token representing the membership of an Internet Protocol (IP) multicast group.

A membership key may represent a membership to receive all datagrams sent to the group, or it may be *source-specific*, meaning that it represents a membership that receives only datagrams from a specific source address. Whether or not a membership key is source-specific may be determined by invoking its `sourceAddress` method.

A membership key is valid upon creation and remains valid until the membership is dropped by invoking the `drop` method, or the channel is closed. The validity of the membership key may be tested by invoking its `isValid` method.

Where a membership key is not source-specific and the underlying operation system supports source filtering, then the `block` and `unblock` methods can be used to block or unblock multicast datagrams from particular source addresses.

Since:

1.7

See Also:

`MulticastChannel`

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	MembershipKey()	Initializes a new instance of this class.

Method Summary

Abstract Methods

Modifier and Type	Method	Description
abstract MembershipKey	block(InetAddress source)	Block multicast datagrams from the given source address.
abstract MulticastChannel	channel()	Returns the channel for which this membership key was created.
abstract void	drop()	Drop membership.
abstract InetAddress	group()	Returns the multicast group for which this membership key was created.
abstract boolean	isValid()	Tells whether or not this membership is valid.
abstract NetworkInterface	networkInterface()	Returns the network interface for which this membership

		key was created.
abstract **InetAddress**	**sourceAddress**()	Returns the source address if this membership key is source-specific, or `null` if this membership is not source-specific.
abstract **MembershipKey**	**unblock**(**InetAddress** source)	Unblock multicast datagrams from the given source address that was previously blocked using the **block** method.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

MembershipKey

```
protected MembershipKey()
```

Initializes a new instance of this class.

Method Detail

isValid

```
public abstract boolean isValid()
```

Tells whether or not this membership is valid.

A multicast group membership is valid upon creation and remains valid until the membership is dropped by invoking the `drop` method, or the channel is closed.

Returns:

`true if this membership key is valid, false otherwise`

drop

```
public abstract void drop()
```

Drop membership.

If the membership key represents a membership to receive all datagrams then the membership is dropped and the channel will no longer receive any datagrams sent to the group. If the membership key is source-specific then the channel will no longer receive datagrams sent to the group from that source address.

After membership is dropped it may still be possible to receive datagrams sent to the group. This can arise when datagrams are waiting to be received in the socket's receive buffer. After membership is dropped then the channel may `join` the group again in which case a new membership key is returned.

Upon return, this membership object will be `invalid`. If the multicast group membership is already invalid then invoking this method has no effect. Once a multicast group membership is invalid, it remains invalid forever.

block

```
public abstract MembershipKey block(InetAddress source)
                             throws IOException
```

Block multicast datagrams from the given source address.

If this membership key is not source-specific, and the underlying operating system supports source filtering, then this method blocks multicast datagrams from the given source address. If the given source address is already blocked then this method has no effect. After a source address is

blocked it may still be possible to receive datagrams from that source. This can arise when datagrams are waiting to be received in the socket's receive buffer.

Parameters:

`source - The source address to block`

Returns:

`This membership key`

Throws:

`IllegalArgumentException - If the source parameter is not a unicast address or is not the same address type as the multicast group`

`IllegalStateException - If this membership key is source-specific or is no longer valid`

`UnsupportedOperationException - If the underlying operating system does not support source filtering`

`IOException - If an I/O error occurs`

unblock

```
public abstract MembershipKey unblock(InetAddress source)
```

Unblock multicast datagrams from the given source address that was previously blocked using the `block` method.

Parameters:

`source - The source address to unblock`

Returns:

`This membership key`

Throws:

`IllegalStateException - If the given source address is not currently blocked or the membership key is no longer valid`

channel

```
public abstract MulticastChannel channel()
```

Returns the channel for which this membership key was created. This method will continue to return the channel even after the membership becomes `invalid`.

Returns:

`the channel`

group

```
public abstract InetAddress group()
```

Returns the multicast group for which this membership key was created. This method will continue to return the group even after the membership becomes `invalid`.

Returns:

the multicast group

networkInterface

```
public abstract NetworkInterface networkInterface()
```

Returns the network interface for which this membership key was created. This method will continue to return the network interface even after the membership becomes `invalid`.

Returns:

the network interface

sourceAddress

```
public abstract InetAddress sourceAddress()
```

Returns the source address if this membership key is source-specific, or `null` if this membership is not source-specific.

Returns:

The source address if this membership key is source-specific, otherwise null

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.