JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.channels

Class Pipe.SourceChannel

java.lang.Object
  java.nio.channels.spi.AbstractInterruptibleChannel
    java.nio.channels.SelectableChannel
      java.nio.channels.spi.AbstractSelectableChannel
        java.nio.channels.Pipe.SourceChannel

All Implemented Interfaces:

`Closeable`, `AutoCloseable`, `Channel`, `InterruptibleChannel`, `ReadableByteChannel`, `ScatteringByteChannel`

Enclosing class:

`Pipe`

```
public abstract static class Pipe.SourceChannel
extends AbstractSelectableChannel
implements ReadableByteChannel, ScatteringByteChannel
```

A channel representing the readable end of a `Pipe`.

Since:

1.4

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	`SourceChannel(SelectorProvider provider)`	Constructs a new instance

		of this class.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
int	**validOps**()	Returns an operation set identifying this channel's supported operations.

Methods inherited from class java.nio.channels.spi.AbstractSelectableChannel

blockingLock, configureBlocking, implCloseChannel, implCloseSelectableChannel, implConfigureBlocking, isBlocking, isRegistered, keyFor, provider, register

Methods inherited from class java.nio.channels.SelectableChannel

register

Methods inherited from class java.nio.channels.spi.AbstractInterruptibleChannel

begin, close, end, isOpen

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.nio.channels.ScatteringByteChannel

read, read

Methods inherited from interface java.nio.channels.ReadableByteChannel

read

Methods inherited from interface java.nio.channels.Channel

close, isOpen

Constructor Detail

SourceChannel

```
protected SourceChannel(SelectorProvider provider)
```

Constructs a new instance of this class.

Parameters:

provider - The selector provider

Method Detail

validOps

```
public final int validOps()
```

Returns an operation set identifying this channel's supported operations.

Pipe-source channels only support reading, so this method returns SelectionKey.OP_READ.

Specified by:

validOps in class SelectableChannel

Returns:

```
The valid-operation set
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.