JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.channels

Class Pipe

java.lang.Object
    java.nio.channels.Pipe

```
public abstract class Pipe
extends Object
```

A pair of channels that implements a unidirectional pipe.

A pipe consists of a pair of channels: A writable `sink` channel and a readable `source` channel. Once some bytes are written to the sink channel they can be read from source channel in exactlyAthe order in which they were written.

Whether or not a thread writing bytes to a pipe will block until another thread reads those bytes, or some previously-written bytes, from the pipe is system-dependent and therefore unspecified. Many pipe implementations will buffer up to a certain number of bytes between the sink and source channels, but such buffering should not be assumed.

Since:

1.4

Nested Class Summary

Nested Classes

Modifier and Type	Class	Description
static class	**Pipe.SinkChannel**	A channel representing the writable end of a **Pipe**.
static class	**Pipe.SourceChannel**	

		A channel representing the readable end of a **Pipe**.

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**Pipe**()	Initializes a new instance of this class.

Method Summary

Instance Methods | **Abstract Methods** | **Concrete Methods**

Modifier and Type	Method	Description
static **Pipe**	**open**()	Opens a pipe.
abstract **Pipe.SinkChannel**	**sink**()	Returns this pipe's sink channel.
abstract **Pipe.SourceChannel**	**source**()	Returns this pipe's source channel.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Pipe

```
protected Pipe()
```

Initializes a new instance of this class.

Method Detail

source

```
public abstract Pipe.SourceChannel source()
```

Returns this pipe's source channel.

Returns:

`This pipe's source channel`

sink

```
public abstract Pipe.SinkChannel sink()
```

Returns this pipe's sink channel.

Returns:

`This pipe's sink channel`

open

```
public static Pipe open()
                  throws IOException
```

Opens a pipe.

The new pipe is created by invoking the `openPipe` method of the system-wide default `SelectorProvider` object.

Returns:

`A new pipe`

Throws:

```
IOException - If an I/O error occurs
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.