JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.channels

Class UnresolvedAddressException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException
          java.nio.channels.UnresolvedAddressException

All Implemented Interfaces:

Serializable

```
public class UnresolvedAddressException
extends IllegalArgumentException
```

Unchecked exception thrown when an attempt is made to invoke a network operation upon an unresolved socket address.

Since:

1.4

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`UnresolvedAddressException()`	Constructs an instance of this class.

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

UnresolvedAddressException

```
public UnresolvedAddressException()
```

Constructs an instance of this class.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.