JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.charset

Class CoderResult

java.lang.Object
    java.nio.charset.CoderResult

```
public class CoderResult
extends Object
```

A description of the result state of a coder.

A charset coder, that is, either a decoder or an encoder, consumes bytes (or characters) from an input buffer, translates them, and writes the resulting characters (or bytes) to an output buffer. A coding process terminates for one of four categories of reasons, which are described by instances of this class:

- *Underflow* is reported when there is no more input to be processed, or there is insufficient input and additional input is required. This condition is represented by the unique result object `UNDERFLOW`, whose `isUnderflow` method returns `true`.
- *Overflow* is reported when there is insufficient room remaining in the output buffer. This condition is represented by the unique result object `OVERFLOW`, whose `isOverflow` method returns `true`.
- A *malformed-input error* is reported when a sequence of input units is not well-formed. Such errors are described by instances of this class whose `isMalformed` method returns `true` and whose `length` method returns the length of the malformed sequence. There is one unique instance of this class for all malformed-input errors of a given length.
- An *unmappable-character error* is reported when a sequence of input units denotes a character that cannot be represented in the output charset. Such errors are described by instances of this class whose `isUnmappable` method returns `true` and whose `length` method returns the length of the input

sequence denoting the unmappable character. There is one unique instance of this class for all unmappable-character errors of a given length.

For convenience, the `isError` method returns `true` for result objects that describe malformed-input and unmappable-character errors but `false` for those that describe underflow or overflow conditions.

Since:

`1.4`

Field Summary

Fields

Modifier and Type	Field	Description
`static CoderResult`	`OVERFLOW`	Result object indicating overflow, meaning that there is insufficient room in the output buffer.
`static CoderResult`	`UNDERFLOW`	Result object indicating underflow, meaning that either the input buffer has been completely consumed or, if the input buffer is not yet empty, that additional input is required.

Method Summary

Concrete Methods **Instance Method**

Modifier and Type	Method	Description
`boolean`	`isError()`	Tells whether or not this object describes an error condition.
`boolean`	`isMalformed()`	Tells whether or not this object describes a malformed-input error.
`boolean`	`isOverflow()`	Tells whether or not this object describes an

		overflow condition.
boolean	**isUnderflow**()	Tells whether or not this object describes an underflow condition.
boolean	**isUnmappable**()	Tells whether or not this object describes an unmappable-character error.
int	**length**()	Returns the length of the erroneous input described by this object *(optional operation)*.
static **CoderResult**	**malformedForLength**(int length)	Static factory method that returns the unique object describing a malformed-input error of the given length.
void	**throwException**()	Throws an exception appropriate to the result described by this object.
String	**toString**()	Returns a string describing this coder result.
static **CoderResult**	**unmappableForLength**(int length)	Static factory method that returns the unique result object describing an

		unmappable-character error of the given length.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Field Detail

UNDERFLOW

```
public static final CoderResult UNDERFLOW
```

Result object indicating underflow, meaning that either the input buffer has been completely consumed or, if the input buffer is not yet empty, that additional input is required.

OVERFLOW

```
public static final CoderResult OVERFLOW
```

Result object indicating overflow, meaning that there is insufficient room in the output buffer.

Method Detail

toString

```
public String toString()
```

Returns a string describing this coder result.

Overrides:

toString in class Object

Returns:

A descriptive string

isUnderflow

```
public boolean isUnderflow()
```

Tells whether or not this object describes an underflow condition.

Returns:

`true if, and only if, this object denotes underflow`

isOverflow

```
public boolean isOverflow()
```

Tells whether or not this object describes an overflow condition.

Returns:

`true if, and only if, this object denotes overflow`

isError

```
public boolean isError()
```

Tells whether or not this object describes an error condition.

Returns:

`true if, and only if, this object denotes either a malformed-input error or an unmappable-character error`

isMalformed

```
public boolean isMalformed()
```

Tells whether or not this object describes a malformed-input error.

Returns:

`true if, and only if, this object denotes a malformed-input error`

isUnmappable

```
public boolean isUnmappable()
```

Tells whether or not this object describes an unmappable-character error.

Returns:

true if, and only if, this object denotes an unmappable-character error

length

public int length()

Returns the length of the erroneous input described by this object *(optional operation)*.

Returns:

The length of the erroneous input, a positive integer

Throws:

UnsupportedOperationException - If this object does not describe an error condition, that is, if the isError does not return true

malformedForLength

public static CoderResult malformedForLength(int length)

Static factory method that returns the unique object describing a malformed-input error of the given length.

Parameters:

length - The given length

Returns:

The requested coder-result object

unmappableForLength

public static CoderResult unmappableForLength(int length)

Static factory method that returns the unique result object describing an unmappable-character error of the given length.

Parameters:

length - The given length

Returns:

The requested coder-result object

throwException

```
public void throwException()
                    throws CharacterCodingException
```

Throws an exception appropriate to the result described by this object.

Throws:

`BufferUnderflowException` - If this object is `UNDERFLOW`

`BufferOverflowException` - If this object is `OVERFLOW`

`MalformedInputException` - If this object represents a malformed-input error; the exception's length value will be that of this object

`UnmappableCharacterException` - If this object represents an unmappable-character error; the exceptions length value will be that of this object

`CharacterCodingException`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.