JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.charset

Class CodingErrorAction

java.lang.Object
    java.nio.charset.CodingErrorAction

```
public class CodingErrorAction
extends Object
```

A typesafe enumeration for coding-error actions.

Instances of this class are used to specify how malformed-input and unmappable-character errors are to be handled by charset decoders and encoders.

Since:

1.4

Field Summary

Fields

Modifier and Type	Field	Description
static CodingErrorAction	IGNORE	Action indicating that a coding error is to be handled by dropping the erroneous input and resuming the coding operation.
static CodingErrorAction	REPLACE	Action indicating that a coding error is to be handled by dropping the erroneous input, appending

		the coder's replacement value to the output buffer, and resuming the coding operation.
static CodingErrorAction	REPORT	Action indicating that a coding error is to be reported, either by returning a CoderResult object or by throwing a CharacterCodingException, whichever is appropriate for the method implementing the coding process.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
String	toString()	Returns a string describing this action.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Field Detail

IGNORE

```
public static final CodingErrorAction IGNORE
```

Action indicating that a coding error is to be handled by dropping the erroneous input and resuming the coding operation.

REPLACE

```
public static final CodingErrorAction REPLACE
```

Action indicating that a coding error is to be handled by dropping the erroneous input, appending the coder's replacement value to the output buffer, and resuming the coding operation.

REPORT

```
public static final CodingErrorAction REPORT
```

Action indicating that a coding error is to be reported, either by returning a `CoderResult` object or by throwing a `CharacterCodingException`, whichever is appropriate for the method implementing the coding process.

Method Detail

toString

```
public String toString()
```

Returns a string describing this action.

Overrides:

`toString` in class `Object`

Returns:

A descriptive string

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.