JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.charset.spi

Class CharsetProvider

java.lang.Object
    java.nio.charset.spi.CharsetProvider

```
public abstract class CharsetProvider
extends Object
```

Charset service-provider class.

A charset provider is a concrete subclass of this class that has a zero-argument constructor and some number of associated charset implementation classes. Charset providers may be installed in an instance of the Java platform as extensions, that is, jar files placed into any of the usual extension directories. Providers may also be made available by adding them to the applet or application class path or by some other platform-specific means. Charset providers are looked up via the current thread's `context class loader`.

A charset provider identifies itself with a provider-configuration file named `java.nio.charset.spi.CharsetProvider` in the resource directory `META-INF/services`. The file should contain a list of fully-qualified concrete charset-provider class names, one per line. A line is terminated by any one of a line feed (`'\n'`), a carriage return (`'\r'`), or a carriage return followed immediately by a line feed. Space and tab characters surrounding each name, as well as blank lines, are ignored. The comment character is `'#'` (`'\u0023'`); on each line all characters following the first comment character are ignored. The file must be encoded in UTF-8.

If a particular concrete charset provider class is named in more than one configuration file, or is named in the same configuration file more than once, then the duplicates will be ignored. The configuration file naming a particular provider need not be in the same jar file or other distribution unit as the provider itself. The provider must be accessible from the same class loader that was initially queried

to locate the configuration file; this is not necessarily the class loader that loaded the file.

Since:

1.4

See Also:

Charset

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	CharsetProvider()	Initializes a new charset provider.

Method Summary

Abstract Methods

Modifier and Type	Method	Description
abstract Charset	charsetForName(String charsetName)	Retrieves a charset for the given charset name.
abstract Iterator<Charset>	charsets()	Creates an iterator that iterates over the charsets supported by this provider.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

CharsetProvider

```
protected CharsetProvider()
```

Initializes a new charset provider.

Throws:

`SecurityException` - If a security manager has been installed and it denies `RuntimePermission("charsetProvider")`

Method Detail

charsets

```
public abstract Iterator<Charset> charsets()
```

Creates an iterator that iterates over the charsets supported by this provider. This method is used in the implementation of the `Charset.availableCharsets` method.

Returns:

The new iterator

charsetForName

```
public abstract Charset charsetForName(String charsetName)
```

Retrieves a charset for the given charset name.

Parameters:

`charsetName` - The name of the requested charset; may be either a canonical name or an alias

Returns:

```
A charset object for the named charset, or null if the named
charset is not supported by this provider
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.